

Undervoltage release, 230 V, non-delayed, 1HP

Part no. FAZ-XUA(230VAC)
212051
EL Number 1695011
(Norway)

General specifications		
Product name		Eaton Distribution parts
Part no.		FAZ-XUA(230VAC)
EAN		4015082120511
Product Length/Depth		80 millimetre
Product height		75.5 millimetre
Product width		17.5 millimetre
Product weight		0.105 kilogram
Compliances		RoHS conform
Certifications		IEC 61373 EN45545-2
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Product Specification Details		
Accessory/spare part type		Undervoltage release
Additional equipment required		Under voltage coil
Ambient operating temperature - max		40 °C
Ambient operating temperature - min		-5 °C
Assembly width		1
Catalog Notes		30VAC
Closing threshold		0.8 x Un
Degree of protection		IP40
Device fitting		Miniature circuit breaker (MCB)
EL number		1695011
Enclosure width		80 mm
Frame		Standard front dimension: 45 mm
Frequency rating		50 Hz / 60 Hz
Functions		Under voltage coil
Mounting width		17.5 mm (1 space unit)
Number of contacts (change-over contacts)		0
Number of contacts (normally closed contacts)		1
Number of contacts (normally open contacts)		1
Number of poles at main contact unit - max		1
Number of switches (fault signal)		0
Rated operational voltage (Ue) - max		230 V
Rated switch current		0 A
Suitable for current of main contact unit - max		0 A
Terminal capacity (cable)		1 mm ² - 2.5 mm ² (2x)
Terminal capacity (solid wire)		1 mm ² - 2.5 mm ² (2x)
Terminal protection		Protection against electric shock to IEC 536
Terminal type		Twin-purpose terminals
Tripping threshold		0.5 x Un
Type		Accessory Accessory for miniature circuit breaker
Used with		Accessory for miniature circuit breaker

		Accessory
Voltage type		AC

Technical data ETIM 9.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)		
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss13-27-14-35-02 [AKE327018])		
Device fitting		Miniature circuit breaker (MCB)
Function		Under voltage coil
Width in number of modular spacings		1
Number of contacts as normally open contact		1
Number of contacts as normally closed contact		1
Number of contacts as change-over contact		0
Number of fault-signal switches		0
Rated switch current	A	0
Rated voltage	V	230
Voltage type		AC
With auto test for earth leakage function		No
Suitable for max. number of poles main contact unit (total)		1
Suitable for max. current main contact unit	A	0