

## Surface mounting enclosure, 1 mounting location

**Part no.** M22-I1  
**216535**  
**EL Number** 4355383  
**(Norway)**

<b>General specifications</b>		
Product name		Eaton Moeller® series M22 Accessory Surface mounting enclosure
Part no.		M22-I1
EAN		4015082165352
Product Length/Depth		74 millimetre
Product height		72 millimetre
Product width		82 millimetre
Product weight		0.134 kilogram
Certifications		CSA-C22.2 No. 14-05 CSA Class No.: 3211-03 UL Category Control No.: NKCR CSA File No.: 012528 UL 508 IEC/EN 60947-5 UL File No.: E29184 CSA CE CSA-C22.2 No. 94-91 UL
Product Tradename		M22
Product Type		Accessory
Product Sub Type		Surface mounting enclosure
<b>Features &amp; Functions</b>		
Enclosure color		Gray
Enclosure material		Plastic
Fitted with:		High-grade steel screws
Knockouts		2 x M16 (cable entry knockouts at the rear) 1 x M20 (cable entry knockout at the top) 2 x M20/25 (cable entry knockout at the side, 1 x each side)
Number of locations		1
RAL-number		7035
<b>General information</b>		
Degree of protection		NEMA 12 IP67/IP69K
Opening diameter		22.5 mm
<b>Climatic environmental conditions</b>		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
<b>Communication</b>		
Connection to SmartWire-DT		No
<b>Contacts</b>		
Force for positive opening - min		0 N
<b>Design verification</b>		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Enclosure for control circuit devices (EC000200)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Housing for command and alarm devices (ecl@ss13-27-37-12-05 [AKF023019])		
Number of command positions		1
Construction type housing		Surface mounted housing
Housing material		Plastic
Housing material quality		Other
Diameter openings	mm	22.5
Colour housing cover		Grey
Degree of protection (IP)		IP67/IP69K
Degree of protection (NEMA)		12
Width	mm	82
Height	mm	72
Depth	mm	74