



Interference-suppression device with cable lengths up to 100m, 6-channel, for 115/230VAC inputs

Part no. EASY256-HCI
Catalog No. 231168
EL-Nummer (Norway) 4520991

Technical data

General

| | | |
|--|------|---|
| Standards | | EN 55011, EN 55022, IEC/EN 61000-4 |
| Dimensions (W x H x D) | mm | 35.5 x 90 x 58 (2 PE) |
| Mounting | | Top-hat rail IEC/EN 60715, 35 mm or screw fixing using fixing brackets ZB4-101-GF1 (accessories) |
| Channels | Qty. | 6 |
| Voltage range at U _e | | 0 - 264 |
| Higher current 115/230 V AC | mA | 4/6 |
| Extension of the switch off delay per EASY input ("1" to "0") 50/60 Hz | ms | 40/37 |
| Cable length | m | 100 |
| Parallel switching of outputs for increased output | | Multiple possibilities (the switch-off delay extends accordingly with the respective number of parallel channels) |
| Type or resistance | | Capitative |

Terminal capacities

| | | |
|------------------------|-----------------|-----------------------|
| Solid | mm ² | 0.2/4 (AWG 22 - 12) |
| Flexible with ferrule | mm ² | 0.2/2.5 (AWG 22 - 12) |
| Standard screwdriver | mm | 0.8 x 3.5 |
| Max. tightening torque | Nm | 0.6 |

Climatic environmental conditions

| | | |
|---|-----|---|
| Operating ambient temperature | °C | -25 to 55, cold as per IEC 60068-2-1, heat as per IEC 60068-2-2 |
| Condensation | | Take appropriate measures to prevent condensation |
| Storage | °C | - 40 - 70 |
| Relative humidity, non-condensing (IEC/EN 60068-2-30) | % | 5 - 95 |
| Air pressure (operation) | hPa | 795 - 1080 |

Ambient conditions, mechanical

| | | |
|--|-------------|------------------------|
| Protection type (IEC/EN 60529, EN50178, VBG 4) | | IP20 |
| Vibrations (IEC/EN 60068-2-6) | Hz | |
| Constant amplitude 0.15 mm | Hz | 10 - 57 |
| Constant acceleration 2 g | Hz | 57 - 150 |
| Mechanical shock resistance (IEC/EN 60068-2-27) semi-sinusoidal 15 g/11 ms | Impacts | 18 |
| Drop to IEC/EN 60068-2-31 | Drop height | mm 50 |
| Free fall, packaged (IEC/EN 60068-2-32) | m | 1 |
| Mounting position | | Vertical or horizontal |

Electromagnetic compatibility (EMC)

| | | |
|---|-----|---|
| Overvoltage category/pollution degree | | II/2 |
| Electrostatic discharge (IEC/EN 61000-4-2, Level 3, ESD) | kV | |
| Air discharge | kV | 8 |
| Contact discharge | kV | 6 |
| Electromagnetic fields (IEC/EN 61000-4-3, RF1) | V/m | 10 |
| Radio interference suppression | | EN 55011 Class B, EN 55022 Class B |
| power pulses (surge) (IEC/EN 61000-4-5, level 2) | kV | 2 (supply cables, symmetrical, EASY...DC) |
| Immunity to line-conducted interference to (IEC/EN 61000-4-6) | V | 10 |

Insulation resistance

| | | |
|---|--|--------------------------------------|
| Clearance in air and creepage distances | | EN 50178, UL 508, CSA C22.2, No. 142 |
| Insulation resistance | | EN 50178 |

Design verification as per IEC/EN 61439

| Technical data for design verification | | | |
|--|------------|----|--|
| Rated operational current for specified heat dissipation | I_n | A | 0 |
| Heat dissipation per pole, current-dependent | P_{vid} | W | 0 |
| Equipment heat dissipation, current-dependent | P_{vid} | W | 0 |
| Static heat dissipation, non-current-dependent | P_{vs} | W | 0 |
| Heat dissipation capacity | P_{diss} | W | 0 |
| Operating ambient temperature min. | | °C | -25 |
| Operating ambient temperature max. | | °C | 55 |
| IEC/EN 61439 design verification | | | |
| 10.2 Strength of materials and parts | | | |
| 10.2.2 Corrosion resistance | | | |
| | | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | | |
| | | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | | |
| | | | Meets the product standard's requirements. |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects | | | |
| | | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | | |
| | | | Meets the product standard's requirements. |
| 10.2.5 Lifting | | | |
| | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | | |
| | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | | |
| | | | Meets the product standard's requirements. |
| 10.3 Degree of protection of ASSEMBLIES | | | |
| | | | Meets the product standard's requirements. |
| 10.4 Clearances and creepage distances | | | |
| | | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | | |
| | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | | |
| | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | | |
| | | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | | |
| | | | Is the panel builder's responsibility. |
| 10.9 Insulation properties | | | |
| 10.9.2 Power-frequency electric strength | | | |
| | | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | | |
| | | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | | |
| | | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | | |
| | | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | | |
| | | | Is the panel builder's responsibility. |
| 10.12 Electromagnetic compatibility | | | |
| | | | Is the panel builder's responsibility. |
| 10.13 Mechanical function | | | |
| | | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 7.0

| | | | |
|---|--|--|-------|
| PLC's (EG000024) / Accessories for controls (EC002584) | | | |
| Electric engineering, automation, process control engineering / Control / Programmable logic control (SPS) / Programmable logic control (SPS, accessories) (ecl@ss10.0.1-27-24-22-92 [AFR333003]) | | | |
| Type of electrical accessory | | | Other |
| Type of mechanical accessory | | | Other |

Approvals

| | | | |
|-----------------------------|--|--|---|
| Product Standards | | | IEC/EN see Technical Data; UL 508; CSA C22.2 No. 142-M1987; CSA C22.2 No. 213-M1987; CE marking |
| UL File No. | | | E135462 |
| UL Category Control No. | | | NRAQ |
| CSA File No. | | | 012528 |
| CSA Class No. | | | 2252-01 |
| North America Certification | | | UL listed, CSA certified |
| Degree of Protection | | | IEC: IP20, UL/CSA Type: - |

Dimensions

