

## Circuit-breaker, 3p, 63A

**Part no.** NZMB1-A63  
**259077**  
**EL Number** 4358702  
**(Norway)**

General specifications		
Product name		Eaton Moeller series NZM molded case circuit breaker thermo-magnetic
Part no.		NZMB1-A63
EAN		4015082590772
Product Length/Depth		88 millimetre
Product height		145 millimetre
Product width		90 millimetre
Product weight		1.051 kilogram
Compliances		RoHS conform
Certifications		IEC IEC/EN 60947
Product Tradename		NZM
Product Type		Molded case circuit breaker
Product Sub Type		Thermo-magnetic
Delivery program		
Application		Use in unearthed supply systems at 440 V
Type		Circuit breaker
Circuit breaker frame type		NZM1
Number of poles		Three-pole
Amperage Rating		63 A
Release system		Thermomagnetic release
Features		Protection unit
Special features		Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I <sub>cn</sub> ) Rated current = rated uninterrupted current: 63 A Terminal capacity hint: Up to 95 mm <sup>2</sup> can be connected depending on the cable manufacturer.
Technical Data - Electrical		
Voltage rating		440 V - 440 V
Rated insulation voltage (U <sub>i</sub> )		690 V AC
Rated impulse withstand voltage (U <sub>imp</sub> ) at auxiliary contacts		6000 V
Rated impulse withstand voltage (U <sub>imp</sub> ) at main contacts		6000 V
Instantaneous current setting (I <sub>i</sub> ) - min		380 A
Instantaneous current setting (I <sub>i</sub> ) - max		630 A
Overload current setting (I <sub>r</sub> ) - min		50 A
Overload current setting (I <sub>r</sub> ) - max		63 A
Short delay current setting (I <sub>sd</sub> ) - min		0 A
Short delay current setting (I <sub>sd</sub> ) - max		0 A
Short-circuit release non-delayed setting - min		378 A
Short-circuit release non-delayed setting - max		630 A
Rated short-circuit breaking capacity I <sub>cs</sub> (IEC/EN 60947) at 230 V, 50/60 Hz		30 kA
Rated short-circuit breaking capacity I <sub>cs</sub> (IEC/EN 60947) at 400/415 V, 50/60 Hz		25 kA
Rated short-circuit breaking capacity I <sub>cs</sub> (IEC/EN 60947) at 440 V, 50/60 Hz		18.5 kA
Rated short-circuit making capacity I <sub>cm</sub> at 240 V, 50/60 Hz		63 kA
Rated short-circuit making capacity I <sub>cm</sub> at 400/415 V, 50/60 Hz		53 kA
Rated short-circuit making capacity I <sub>cm</sub> at 440 V, 50/60 Hz		53 kA
Short-circuit total breaktime		< 10 ms
Electrical connection type of main circuit		Frame clamp
Isolation		500 V AC (between auxiliary contacts and main contacts)

		300 V AC (between the auxiliary contacts)
Number of operations per hour - max		120
Handle type		Rocker lever
Utilization category		A (IEC/EN 60947-2)
Overvoltage category		III
Pollution degree		3
Lifespan, electrical		7500 operations at 415 V AC-1 7500 operations at 400 V AC-1
Direction of incoming supply		As required
<b>Technical Data - Mechanical</b>		
Mounting Method		DIN rail (top hat rail) mounting optional Fixed Built-in device fixed built-in technique
Degree of protection		IP20 (basic degree of protection, in the operating controls area) IP20
Degree of protection (IP), front side		IP40 (with insulating surround) IP66 (with door coupling rotary handle)
Degree of protection (terminations)		IP10 (tunnel terminal) IP00 (terminations, phase isolator and strip terminal)
Protection against direct contact		Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110
Shock resistance		20 g (half-sinusoidal shock 20 ms)
Number of auxiliary contacts (change-over contacts)		0
Number of auxiliary contacts (normally closed contacts)		0
Number of auxiliary contacts (normally open contacts)		0
Position of connection for main current circuit		Front side
Climatic proofing		Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Special features		Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I <sub>cn</sub> ) Rated current = rated uninterrupted current: 63 A Terminal capacity hint: Up to 95 mm <sup>2</sup> can be connected depending on the cable manufacturer.
Lifespan, mechanical		20000 operations
<b>Technical Data - Mechanical - Terminals</b>		
Standard terminals		Box terminal
Optional terminals		Connection on rear. Screw terminal. Tunnel terminal
Terminal capacity (control cable)		0.75 mm <sup>2</sup> - 2.5 mm <sup>2</sup> (1x) 0.75 mm <sup>2</sup> - 1.5 mm <sup>2</sup> (2x)
Terminal capacity (aluminum solid conductor/cable)		10 mm <sup>2</sup> - 16 mm <sup>2</sup> (2x) direct at switch rear-side connection 16 mm <sup>2</sup> (1x) at tunnel terminal 10 mm <sup>2</sup> - 16 mm <sup>2</sup> (1x) direct at switch rear-side connection
Terminal capacity (aluminum stranded conductor/cable)		25 mm <sup>2</sup> - 95 mm <sup>2</sup> (1x) at tunnel terminal 25 mm <sup>2</sup> - 35 mm <sup>2</sup> (2x) direct at switch rear-side connection 25 mm <sup>2</sup> - 35 mm <sup>2</sup> (1x) direct at switch rear-side connection
Terminal capacity (copper busbar)		M6 at rear-side screw connection Min. 12 mm x 5 mm direct at switch rear-side connection Max. 16 mm x 5 mm direct at switch rear-side connection
Terminal capacity (copper solid conductor/cable)		16 mm <sup>2</sup> (1x) at tunnel terminal 10 mm <sup>2</sup> - 16 mm <sup>2</sup> (1x) at box terminal 10 mm <sup>2</sup> - 16 mm <sup>2</sup> (1x) direct at switch rear-side connection 6 mm <sup>2</sup> - 16 mm <sup>2</sup> (2x) at box terminal 6 mm <sup>2</sup> - 16 mm <sup>2</sup> (2x) direct at switch rear-side connection
Terminal capacity (copper stranded conductor/cable)		10 mm <sup>2</sup> - 70 mm <sup>2</sup> (1x) at box terminal 25 mm <sup>2</sup> - 95 mm <sup>2</sup> (1x) at 1-hole tunnel terminal 25 mm <sup>2</sup> (2x) direct at switch rear-side connection 6 mm <sup>2</sup> - 25 mm <sup>2</sup> (2x) at box terminal 10 mm <sup>2</sup> - 70 mm <sup>2</sup> (1x) direct at switch rear-side connection
Terminal capacity (copper strip)		Min. 2 segments of 9 mm x 0.8 mm at box terminal Max. 9 segments of 9 mm x 0.8 mm at box terminal
<b>Design verification as per IEC/EN 61439 - technical data</b>		
Rated operational current for specified heat dissipation (I <sub>n</sub> )		63 A
Equipment heat dissipation, current-dependent		14.17 W
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Ambient storage temperature - min		40 °C
Ambient storage temperature - max		70 °C

<b>Design verification as per IEC/EN 61439</b>		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>Additional information</b>		
Functions		System and cable protection

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EC000228)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecl@ss13-27-37-04-09 [AJZ716018])		
Rated permanent current I <sub>u</sub>	A	63
Rated voltage	V	440 - 440
Rated short-circuit breaking capacity I <sub>cu</sub> at 400 V, 50 Hz	kA	25
Overload release current setting	A	50 - 63
Adjustment range short-term delayed short-circuit release	A	0 - 0
Adjustment range undelayed short-circuit release	A	380 - 630
Power loss	W	14.2
Device construction		Built-in device fixed built-in technique
Integrated earth fault protection		No
Type of electrical connection of main circuit		Frame clamp
Suitable for DIN rail (top hat rail) mounting		No
DIN rail (top hat rail) mounting optional		Yes
Number of auxiliary contacts as normally closed contact		0
Number of auxiliary contacts as normally open contact		0
Number of auxiliary contacts as change-over contact		0
With switched-off indicator		No
With integrated under voltage release		No
Number of poles		3
Position of connection for main current circuit		Front side
Type of control element		Rocker lever
Complete device with protection unit		Yes
Motor drive integrated		No
Motor drive optional		No
Degree of protection (IP)		IP20

