

Screw connection, 3p, standard, size 3



**Part no.** NZM3-XKS  
**260039**  
**EL Number** 4358777  
**(Norway)**

General specifications		
Product name		Eaton Moeller series NZM connection type
Part no.		NZM3-XKS
EAN		4015082600396
Product Length/Depth		120.5 millimetre
Product height		459 millimetre
Product width		140 millimetre
Product weight		0.14 kilogram
Compliances		IEC UL/CSA RoHS conform
Certifications		UL (Category Control Number DIHS) CSA-C22.2 No. 5-09 CE marking CSA (Class No. 1437-01) UL listed UL (File No. E31593) CSA (File No. 22086) UL489 CSA certified IEC60947
Product Tradename		NZM
Product Type		Accessories
Product Sub Type		Connection type
Delivery program		
Type		Accessory Screw connection Terminal
Number of poles		Three-pole
Amperage Rating		630 A
Frame		NZM3
Suitable for		Copper cable lugs Three-pole Aluminum cable lug
Used with		NZM3, PN3, N(S)3
Technical Data - Mechanical - Terminals		
Terminal capacity (stranded cable)		16 mm <sup>2</sup> - 300 mm <sup>2</sup> (1x) 4 - 350 AWG/kcmil (1x) 16 mm <sup>2</sup> - 240 mm <sup>2</sup> (2x) 350 AWG/kcmil (2x)
Terminal capacity (copper busbar)		30 mm x 10 mm + 30 mm x 5 mm
Terminal capacity (copper strip)		10 segments of 32 mm x 1 mm + 5 segments of 32 mm x 1 mm
Design verification as per IEC/EN 61439		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.

10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>Additional information</b>			
Model			Other

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Wiring set for power circuit breaker (EC002050)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Wiring set for circuit breaker (ecl@ss13-27-37-04-24 [ACN957016])			
Suitable for number of poles			3
Model			Other