




LED, BA 9s green, 12-30VAC/DC, 15mA

**Part no.** A22-LED-G  
**Catalog No.** 261363  
**Alternate Catalog No.** A22-LED-G

**Delivery program**

|   |                 |   |   |
|---|-----------------|---|---|
| Accessories                                   |                 |   | General accessories   |
| Basic function accessories                    |                 |   | Single chip LED   |
| Type  |                 |   | For AC and DC voltage (positive pole connected to X1) protected against polarity reversal integral circuit-breaker up to 1500 V |
| Lifespan to EN 60064 at $t_a = +25\text{ °C}$ | $t_{mean}$ (AC) | h | 12 - 30 V AC/DC/15 mA<br>100000   |
| <b>Colour</b>                                 |                 |   |   |
| Connection to SmartWire-DT                    |                 |   | no  |

**Technical data**

**General**

|                     |  |                 |            |
|---------------------|--|-----------------|------------|
| Ambient temperature |  |                 |            |
| Open                |  | °C              | -25 - +70  |
| Terminal capacities |  | mm <sup>2</sup> |            |
| Solid               |  | mm <sup>2</sup> | 0.75 - 2.5 |
| Stranded            |  | mm <sup>2</sup> | 0.5 - 2.5  |

**Contacts**

|                                       |           |      |       |
|---------------------------------------|-----------|------|-------|
| Rated impulse withstand voltage       | $U_{imp}$ | V AC | 6000  |
| Rated insulation voltage              | $U_i$     | V    | 500   |
| Overvoltage category/pollution degree |           |      | III/3 |

**Design verification as per IEC/EN 61439**

|  |  |    |     |
|--|--|----|-----|
| Technical data for design verification |  |    |     |
| Operating ambient temperature min.     |  | °C | -25 |
| Operating ambient temperature max.     |  | °C | 70  |

**Technical data ETIM 7.0**

|   |  |    |         |
|---|--|----|---------|
| Lamps (EG000028) / Indication- and signalling lamp (EC000399)   |  |    |         |
| Electric engineering, automation, process control engineering / Lighting installation, device / Light medium / Indication- and signal lamp (ec1@ss10.0.1-27-11-06-31 [AKE242014]) |  |    |         |
| Lamp power  |  | W  |         |
| Lamp voltage  |  | V  | 24 - 30 |
| Luminous flux   |  | lm | 0       |
| Socket  |  |    | BA9s    |
| Technology  |  |    | LED     |
| Lamp shape  |  |    | Other   |
| Halogen   |  |    | No      |
| Krypton   |  |    | No      |
| Xenon   |  |    | No      |
| Colour  |  |    | Green   |
| Colour temperature  |  | K  | 0       |

|                                       |    |        |
|---------------------------------------|----|--------|
| Diameter                              | mm | 0      |
| Total length                          | mm | 0      |
| Suitable for torches                  |    | No     |
| Suitable for pointer                  |    | Yes    |
| Suitable for round flashing luminaire |    |        |
| Nominal current                       | mA | 15     |
| Average nominal lifespan              | h  | 100000 |
| Energy efficiency class               |    |        |