



Phase busbar, 4-phases, 16qmm, pin, 1m

Part no. Z-SV-16/3P+3N-3TE
 Catalog No. 264915

Technical data ETIM 7.0

| | | | |
|---|--|-----------------|------|
| Low-voltage industrial components (EG000017) / Phase busbar (EC000215) | | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ec@ss10.0.1-27-37-13-06 [ACN992011]) | | | |
| Number of phases | | | 3 |
| Number of poles | | | 3 |
| Suitable for number of devices | | | 0 |
| Pitch dimensions | | mm | 17.8 |
| Cross section | | mm ² | 16 |
| Length | | mm | 1000 |
| Number of modular spacings | | | 3 |
| Rated permanent current I _u | | A | 63 |
| Type of electric connection | | | Pin |
| Insulated | | | Yes |
| Rated surge voltage | | kV | 4 |
| Conditioned rated short-circuit current I _q | | kA | 0 |
| Max. rated operation voltage U _e | | V | 415 |
| Rated short-time withstand current I _{cw} | | kA | 0 |
| Suitable for devices with N-busbar | | | No |
| Suitable for devices with auxiliary switch | | | No |