

Circuit-breaker, 3p, 630A



Part no. **NZMN4-AE630**
265758

General specifications		
Product name		Eaton Moeller series NZM molded case circuit breaker electronic
Part no.		NZMN4-AE630
EAN		4015082657581
Product Length/Depth		401 millimetre
Product height		207 millimetre
Product width		210 millimetre
Product weight		15.52 kilogram
Compliances		RoHS conform
Certifications		IEC IEC/EN 60947
Product Tradename		NZM
Product Type		Molded case circuit breaker
Product Sub Type		Electronic
Delivery program		
Application		Use in unearthed supply systems at 525 V
Type		Circuit breaker
Circuit breaker frame type		NZM4
Number of poles		Three-pole
Amperage Rating		630 A
Release system		Electronic release
Features		Motor drive optional Protection unit
Special features		Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I _{cn}) R.m.s. value measurement and "thermal memory" Rated current = rated uninterrupted current: 630 A
Technical Data - Electrical		
Voltage rating		690 V - 690 V
Rated insulation voltage (U _i)		1000 V AC
Rated impulse withstand voltage (U _{imp}) at auxiliary contacts		6000 V
Rated impulse withstand voltage (U _{imp}) at main contacts		8000 V
Rated short-time withstand current (t = 0.3 s)		12 kA
Rated short-time withstand current (t = 1 s)		12 kA
Instantaneous current setting (I _i) - min		1260 A
Instantaneous current setting (I _i) - max		7560 A
Overload current setting (I _r) - min		315 A
Overload current setting (I _r) - max		630 A
Short delay current setting (I _{sd}) - min		0 A
Short delay current setting (I _{sd}) - max		0 A
Short-circuit release non-delayed setting - min		1260 A
Short-circuit release non-delayed setting - max		11340 A
Rated short-circuit breaking capacity I _{cs} (IEC/EN 60947) at 230 V, 50/60 Hz		37 kA
Rated short-circuit breaking capacity I _{cs} (IEC/EN 60947) at 400/415 V, 50/60 Hz		37 kA
Rated short-circuit breaking capacity I _{cs} (IEC/EN 60947) at 440 V, 50/60 Hz		26 kA
Rated short-circuit breaking capacity I _{cs} (IEC/EN 60947) at 525 V, 50/60 Hz		19 kA
Rated short-circuit breaking capacity I _{cs} (IEC/EN 60947) at 690 V, 50/60 Hz		15 kA
Rated short-circuit making capacity I _{cm} at 240 V, 50/60 Hz		105 kA
Rated short-circuit making capacity I _{cm} at 400/415 V, 50/60 Hz		105 kA
Rated short-circuit making capacity I _{cm} at 440 V, 50/60 Hz		74 kA

Rated short-circuit making capacity I _{cm} at 525 V, 50/60 Hz		53 kA
Rated short-circuit making capacity I _{cm} at 690 V, 50/60 Hz		40 kA
Short-circuit total breaktime		< 25 ms (≤ 415 V); < 35 ms (> 415 V)
Electrical connection type of main circuit		Screw connection
Isolation		500 V AC (between auxiliary contacts and main contacts) 300 V AC (between the auxiliary contacts)
Number of operations per hour - max		60
Handle type		Rocker lever
Utilization category		A (IEC/EN 60947-2)
Overvoltage category		III
Pollution degree		3
Lifespan, electrical		2000 operations at 415 V AC-3 2000 operations at 400 V AC-3 3000 operations at 400 V AC-1 3000 operations at 415 V AC-1 1000 operations at 690 V AC-3 2000 operations at 690 V AC-1
Direction of incoming supply		As required
Technical Data - Mechanical		
Mounting Method		Fixed Built-in device fixed built-in technique
Degree of protection		IP20 IP20 (basic degree of protection, in the operating controls area)
Degree of protection (IP), front side		IP66 (with door coupling rotary handle) IP40 (with insulating surround)
Degree of protection (terminations)		IP00 (terminations, phase isolator and strip terminal) IP10 (tunnel terminal)
Protection against direct contact		Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110
Shock resistance		15 g (half-sinusoidal shock 11 ms)
Number of auxiliary contacts (change-over contacts)		0
Number of auxiliary contacts (normally closed contacts)		0
Number of auxiliary contacts (normally open contacts)		0
Position of connection for main current circuit		Front side
Climatic proofing		Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Special features		Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I _{cn}) R.m.s. value measurement and "thermal memory" Rated current = rated uninterrupted current: 630 A
Lifespan, mechanical		10000 operations
Technical Data - Mechanical - Terminals		
Standard terminals		Screw terminal
Optional terminals		Connection on rear. Strip terminal. Tunnel terminal
Terminal capacity (control cable)		0.75 mm ² - 2.5 mm ² (1x) 0.75 mm ² - 1.5 mm ² (2x)
Terminal capacity (aluminum solid conductor/cable)		240 mm ² (2x) at rear-side width extension 50 mm ² (4x) at rear-side 2-hole module plate 70 mm ² - 185 mm ² (2x) at rear-side 1-hole module plate 185 mm ² - 240 mm ² (1x) at rear-side 1-hole module plate 70 mm ² - 240 mm ² (6x) at rear-side width extension
Terminal capacity (aluminum stranded conductor/cable)		50 mm ² - 240 mm ² (4x) at 4-hole tunnel terminal
Terminal capacity (copper busbar)		Max. 80 mm x 10 mm (2x) at rear-side width extension Min. 60 mm x 10 mm at rear-side width extension Max. 50 mm x 10 mm (2x) at rear-side 1-hole module plate 50 mm x 10 mm (2x) at rear-side 2-hole module plate Min. 25 mm x 5 mm at rear-side 1-hole module plate Max. 50 mm x 10 mm (2x) direct at switch rear-side connection Min. 25 mm x 5 mm direct at switch rear-side connection M10 at rear-side screw connection
Terminal capacity (copper solid conductor/cable)		95 mm ² - 185 mm ² (2x) at rear-side 2-hole module plate 120 mm ² - 300 mm ² (1x) at rear-side 1-hole module plate 95 mm ² - 300 mm ² (2x) at rear-side 1-hole module plate 95 mm ² - 240 mm ² (6x) at rear-side width extension 35 mm ² - 185 mm ² (4x) at rear-side 2-hole module plate 300 mm ² (4x) at rear-side width extension 50 mm ² - 240 mm ² (4x) at 4-hole tunnel terminal
Terminal capacity (copper stranded conductor/cable)		120 mm ² - 185 mm ² (1x) direct at switch rear-side connection 50 mm ² - 185 mm ² (4x) direct at switch rear-side connection

Terminal capacity (copper strip)		Max. 10 segments of 32 mm x 1 mm (2x) at flat conductor terminal 10 segments of 50 mm x 1 mm (2x) at 1-hole module plate Min. 6 segments of 16 mm x 0.8 mm at flat conductor terminal Max. 10 segments of 50 mm x 1 mm (2x) at rear-side connection (punched) Min. 5 segments of 25 mm x 1 mm at rear-side connection (punched) 10 segments of 80 mm x 1 mm (2x) at rear-side width extension
Design verification as per IEC/EN 61439 - technical data		
Rated operational current for specified heat dissipation (In)		630 A
Equipment heat dissipation, current-dependent		65 W
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Ambient storage temperature - min		40 °C
Ambient storage temperature - max		70 °C
Design verification as per IEC/EN 61439		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
Additional information		
Functions		System and cable protection

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EC000228)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecf@ss13-27-37-04-09 [AJZ716018])		
Rated permanent current Iu	A	630
Rated voltage	V	690 - 690
Rated short-circuit breaking capacity Icu at 400 V, 50 Hz	kA	37
Overload release current setting	A	315 - 630
Adjustment range short-term delayed short-circuit release	A	0 - 0
Adjustment range undelayed short-circuit release	A	1260 - 7560
Power loss	W	
Device construction		Built-in device fixed built-in technique
Integrated earth fault protection		No
Type of electrical connection of main circuit		Screw connection
Suitable for DIN rail (top hat rail) mounting		No
DIN rail (top hat rail) mounting optional		No
Number of auxiliary contacts as normally closed contact		0

Number of auxiliary contacts as normally open contact			0
Number of auxiliary contacts as change-over contact			0
With switched-off indicator			No
With integrated under voltage release			No
Number of poles			3
Position of connection for main current circuit			Front side
Type of control element			Rocker lever
Complete device with protection unit			Yes
Motor drive integrated			No
Motor drive optional			Yes
Degree of protection (IP)			IP20