

Circuit-breaker, 4p, 200A, 125A in 4th pole



**Part no. NZMH2-4-A200/125  
265875**

| General specifications  |   |
|---|---|
| Product name  | Eaton Moeller series NZM molded case circuit breaker thermo-magnetic  |
| Part no.  | NZMH2-4-A200/125  |
| EAN   | 4015082658755   |
| Product Length/Depth  | 149 millimetre  |
| Product height  | 184 millimetre  |
| Product width   | 140 millimetre  |
| Product weight  | 3 kilogram  |
| Compliances   | RoHS conform  |
| Certifications  | IEC/EN 60947<br>IEC   |
| Product Tradename   | NZM   |
| Product Type  | Molded case circuit breaker   |
| Product Sub Type  | Thermo-magnetic   |
| Delivery program  |   |
| Application   | Use in unearthed supply systems at 690 V  |
| Type  | Circuit breaker   |
| Circuit breaker frame type  | NZM2  |
| Number of poles   | Four-pole   |
| Amperage Rating   | 200 A   |
| Release system  | Thermomagnetic release  |
| Features  | Motor drive optional<br>Protection unit   |
| Special features  | Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I <sub>cs</sub> ) Rated current = rated uninterrupted current: 200 A Reduced neutral conductor protection Set value in neutral conductor is synchronous with set value I <sub>r</sub> of main pole. |
| Technical Data - Electrical   |   |
| Voltage rating  | 690 V - 690 V   |
| Rated insulation voltage (U <sub>i</sub> )  | 1000 V AC   |
| Rated impulse withstand voltage (U <sub>imp</sub> ) at auxiliary contacts                   | 6000 V  |
| Rated impulse withstand voltage (U <sub>imp</sub> ) at main contacts                        | 8000 V  |
| Current rating of neutral conductor   | 125 A<br>60% of phase conductor   |
| Rated short-time withstand current (t = 0.3 s)  | 1.9 kA  |
| Rated short-time withstand current (t = 1 s)  | 1.9 kA  |
| Instantaneous current setting (I <sub>i</sub> ) - min                                       | 6 A   |
| Instantaneous current setting (I <sub>i</sub> ) - max                                       | 10 A  |
| Overload current setting (I <sub>r</sub> )  | 100 A - 125 A   |
| Overload current setting (I <sub>r</sub> ) - min  | 160 A   |
| Overload current setting (I <sub>r</sub> ) - max  | 200 A   |
| Short delay current setting (I <sub>sd</sub> ) - min  | 0 A   |
| Short delay current setting (I <sub>sd</sub> ) - max  | 0 A   |
| Short-circuit release non-delayed setting - min   | 1200 A  |
| Short-circuit release non-delayed setting - max   | 2000 A  |
| Rated short-circuit breaking capacity I <sub>cs</sub> (IEC/EN 60947) at 230 V, 50/60 Hz     | 150 kA  |
| Rated short-circuit breaking capacity I <sub>cs</sub> (IEC/EN 60947) at 400/415 V, 50/60 Hz | 150 kA  |
| Rated short-circuit breaking capacity I <sub>cs</sub> (IEC/EN 60947) at 440 V, 50/60 Hz     | 130 kA  |
| Rated short-circuit breaking capacity I <sub>cs</sub> (IEC/EN 60947) at 525 V, 50/60 Hz     | 37.5 kA   |
| Rated short-circuit breaking capacity I <sub>cs</sub> (IEC/EN 60947) at 690 V, 50/60 Hz     | 5 kA  |

|  |  |   |
|--|--|---|
| Rated short-circuit making capacity I <sub>cm</sub> at 240 V, 50/60 Hz     |  | 330 kA  |
| Rated short-circuit making capacity I <sub>cm</sub> at 400/415 V, 50/60 Hz |  | 330 kA  |
| Rated short-circuit making capacity I <sub>cm</sub> at 440 V, 50/60 Hz     |  | 286 kA  |
| Rated short-circuit making capacity I <sub>cm</sub> at 525 V, 50/60 Hz     |  | 105 kA  |
| Rated short-circuit making capacity I <sub>cm</sub> at 690 V, 50/60 Hz     |  | 40 kA   |
| Short-circuit total breaktime  |  | < 10 ms   |
| Electrical connection type of main circuit                                 |  | Screw connection  |
| Isolation  |  | 300 V AC (between the auxiliary contacts)<br>500 V AC (between auxiliary contacts and main contacts)  |
| Number of operations per hour - max  |  | 120   |
| Handle type  |  | Rocker lever  |
| Utilization category   |  | A (IEC/EN 60947-2)  |
| Overvoltage category   |  | III   |
| Pollution degree   |  | 3   |
| Lifespan, electrical   |  | 6500 operations at 415 V AC-3<br>10000 operations at 400 V AC-1<br>6500 operations at 400 V AC-3<br>10000 operations at 415 V AC-1<br>5000 operations at 690 V AC-3<br>7500 operations at 690 V AC-1  |
| Direction of incoming supply   |  | As required   |
| <b>Technical Data - Mechanical</b>   |  |   |
| Mounting Method  |  | Built-in device fixed built-in technique<br>Fixed<br>DIN rail (top hat rail) mounting optional  |
| Degree of protection   |  | IP20<br>IP20 (basic degree of protection, in the operating controls area)   |
| Degree of protection (IP), front side                                      |  | IP66 (with door coupling rotary handle)<br>IP40 (with insulating surround)  |
| Degree of protection (terminations)  |  | IP00 (terminations, phase isolator and strip terminal)<br>IP10 (tunnel terminal)  |
| Protection against direct contact  |  | Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110   |
| Shock resistance   |  | 20 g (half-sinusoidal shock 20 ms)  |
| Number of auxiliary contacts (change-over contacts)                        |  | 0   |
| Number of auxiliary contacts (normally closed contacts)                    |  | 0   |
| Number of auxiliary contacts (normally open contacts)                      |  | 0   |
| Position of connection for main current circuit                            |  | Front side  |
| Climatic proofing  |  | Damp heat, cyclic, to IEC 60068-2-30<br>Damp heat, constant, to IEC 60068-2-78  |
| Special features   |  | Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I <sub>cn</sub> ) Rated current = rated uninterrupted current: 200 A Reduced neutral conductor protection Set value in neutral conductor is synchronous with set value I <sub>r</sub> of main pole. |
| Lifespan, mechanical   |  | 20000 operations  |
| <b>Technical Data - Mechanical - Terminals</b>                             |  |   |
| Standard terminals   |  | Screw terminal  |
| Optional terminals   |  | Box terminal. Connection on rear. Tunnel terminal   |
| Terminal capacity (control cable)  |  | 0.75 mm <sup>2</sup> - 1.5 mm <sup>2</sup> (2x)<br>0.75 mm <sup>2</sup> - 2.5 mm <sup>2</sup> (1x)  |
| Terminal capacity (aluminum solid conductor/cable)                         |  | 10 mm <sup>2</sup> - 16 mm <sup>2</sup> (2x) direct at switch rear-side connection<br>10 mm <sup>2</sup> - 16 mm <sup>2</sup> (1x) direct at switch rear-side connection<br>16 mm <sup>2</sup> (1x) at tunnel terminal  |
| Terminal capacity (aluminum stranded conductor/cable)                      |  | 25 mm <sup>2</sup> - 50 mm <sup>2</sup> (2x) direct at switch rear-side connection<br>25 mm <sup>2</sup> - 185 mm <sup>2</sup> (1x) at tunnel terminal<br>25 mm <sup>2</sup> - 50 mm <sup>2</sup> (1x) direct at switch rear-side connection  |
| Terminal capacity (copper busbar)  |  | Max. 24 mm x 8 mm direct at switch rear-side connection<br>M8 at rear-side screw connection<br>Min. 16 mm x 5 mm direct at switch rear-side connection  |
| Terminal capacity (copper solid conductor/cable)                           |  | 6 mm <sup>2</sup> - 16 mm <sup>2</sup> (2x) at box terminal<br>16 mm <sup>2</sup> (1x) at tunnel terminal<br>10 mm <sup>2</sup> - 16 mm <sup>2</sup> (1x) at box terminal<br>10 mm <sup>2</sup> - 16 mm <sup>2</sup> (1x) direct at switch rear-side connection<br>6 mm <sup>2</sup> - 16 mm <sup>2</sup> (2x) direct at switch rear-side connection                                      |
| Terminal capacity (copper stranded conductor/cable)                        |  | 25 mm <sup>2</sup> - 70 mm <sup>2</sup> (2x) direct at switch rear-side connection<br>25 mm <sup>2</sup> - 185 mm <sup>2</sup> (1x) direct at switch rear-side connection<br>25 mm <sup>2</sup> - 185 mm <sup>2</sup> (1x) at box terminal<br>25 mm <sup>2</sup> - 185 mm <sup>2</sup> (1x) at 1-hole tunnel terminal   |

|  |  |   |
|--|--|---|
| Terminal capacity (copper strip)   |  | 25 mm <sup>2</sup> - 70 mm <sup>2</sup> (2x) at box terminal<br>Max. 8 segments of 24 mm x 1 mm (2x) at box terminal<br>Max. 10 segments of 16 mm x 0.8 mm at box terminal<br>Max. 10 segments of 24 mm x 0.8 mm at rear-side connection (punched)<br>Min. 2 segments of 16 mm x 0.8 mm at rear-side connection (punched)<br>Min. 2 segments of 9 mm x 0.8 mm at box terminal |
| <b>Design verification as per IEC/EN 61439 - technical data</b>                  |  |   |
| Rated operational current for specified heat dissipation (In)                    |  | 200 A   |
| Equipment heat dissipation, current-dependent                                    |  | 48 W  |
| Ambient operating temperature - min  |  | -25 °C  |
| Ambient operating temperature - max  |  | 70 °C   |
| Ambient storage temperature - min  |  | -40 °C  |
| Ambient storage temperature - max  |  | 70 °C   |
| <b>Design verification as per IEC/EN 61439</b>                                   |  |   |
| 10.2.2 Corrosion resistance  |  | Meets the product standard's requirements.  |
| 10.2.3.1 Verification of thermal stability of enclosures                         |  | Meets the product standard's requirements.  |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat       |  | Meets the product standard's requirements.  |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects |  | Meets the product standard's requirements.  |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                 |  | Meets the product standard's requirements.  |
| 10.2.5 Lifting   |  | Does not apply, since the entire switchgear needs to be evaluated.  |
| 10.2.6 Mechanical impact   |  | Does not apply, since the entire switchgear needs to be evaluated.  |
| 10.2.7 Inscriptions  |  | Meets the product standard's requirements.  |
| 10.3 Degree of protection of assemblies  |  | Does not apply, since the entire switchgear needs to be evaluated.  |
| 10.4 Clearances and creepage distances   |  | Meets the product standard's requirements.  |
| 10.5 Protection against electric shock   |  | Does not apply, since the entire switchgear needs to be evaluated.  |
| 10.6 Incorporation of switching devices and components                           |  | Does not apply, since the entire switchgear needs to be evaluated.  |
| 10.7 Internal electrical circuits and connections                                |  | Is the panel builder's responsibility.  |
| 10.8 Connections for external conductors   |  | Is the panel builder's responsibility.  |
| 10.9.2 Power-frequency electric strength   |  | Is the panel builder's responsibility.  |
| 10.9.3 Impulse withstand voltage   |  | Is the panel builder's responsibility.  |
| 10.9.4 Testing of enclosures made of insulating material                         |  | Is the panel builder's responsibility.  |
| 10.10 Temperature rise   |  | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.  |
| 10.11 Short-circuit rating   |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.  |
| 10.12 Electromagnetic compatibility  |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.  |
| 10.13 Mechanical function  |  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.  |
| <b>Additional information</b>  |  |   |
| Functions  |  | System and cable protection   |

## Technical data ETIM 9.0

|   |    |  |
|---|----|--|
| Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EC000228)   |    |  |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecl@ss13-27-37-04-09 [AJZ716018]) |    |  |
| Rated permanent current Iu  | A  | 200                                      |
| Rated voltage   | V  | 690 - 690                                |
| Rated short-circuit breaking capacity Icu at 400 V, 50 Hz   | kA | 150                                      |
| Overload release current setting  | A  | 160 - 200                                |
| Adjustment range short-term delayed short-circuit release   | A  | 0 - 0                                    |
| Adjustment range undelayed short-circuit release  | A  | 6 - 10                                   |
| Power loss  | W  |  |
| Device construction   |    | Built-in device fixed built-in technique |
| Integrated earth fault protection   |    | No                                       |
| Type of electrical connection of main circuit   |    | Screw connection                         |
| Suitable for DIN rail (top hat rail) mounting   |    | No                                       |
| DIN rail (top hat rail) mounting optional   |    | Yes                                      |
| Number of auxiliary contacts as normally closed contact   |    | 0  |

|   |  |  |              |
|---|--|--|--------------|
| Number of auxiliary contacts as normally open contact |  |  | 0            |
| Number of auxiliary contacts as change-over contact   |  |  | 0            |
| With switched-off indicator                           |  |  | No           |
| With integrated under voltage release                 |  |  | No           |
| Number of poles                                       |  |  | 4            |
| Position of connection for main current circuit       |  |  | Front side   |
| Type of control element                               |  |  | Rocker lever |
| Complete device with protection unit                  |  |  | Yes          |
| Motor drive integrated                                |  |  | No           |
| Motor drive optional                                  |  |  | Yes          |
| Degree of protection (IP)                             |  |  | IP20         |