

**Additional plate**

**Part no. NZM1/2-XZB  
266676**



|  |  |   |
|--|--|---|
| <b>General specifications</b>  |  |   |
| Product name   |  | Eaton Moeller series NZM operating element accessory  |
| Part no.   |  | NZM1/2-XZB  |
| EAN  |  | 4015082666767   |
| Product Length/Depth   |  | 145 millimetre  |
| Product height   |  | 3 millimetre  |
| Product width  |  | 50 millimetre   |
| Product weight   |  | 0.176 kilogram  |
| Compliances  |  | IEC<br>UL/CSA<br>RoHS conform   |
| Product Tradename  |  | NZM   |
| Product Type   |  | Accessories   |
| Product Sub Type   |  | Operating element accessory   |
| <b>Delivery program</b>  |  |   |
| Type   |  | Accessory<br>Additional plate   |
| Features   |  | For fitting to the mounting bracket when using N conductor or PE conductor terminals K25, K50, K95 or K150  |
| Special features   |  | Additional terminal arrangement for sidewall drive with mounting bracket<br>For fitting to the mounting bracket when using N conductor or PE conductor terminals K50/1, K95/... or K150/... |
| Frame  |  | NZM1/2  |
| Suitable for   |  | Switch disconnecter<br>Power circuit breaker  |
| Used with  |  | NZM1-4<br>PN1<br>PN2-4<br>NZM1<br>NZM1-NA<br>NZM2<br>NZM2-4<br>NS1<br>N2<br>N1-4<br>N2-4<br>NZM2-NA<br>PN1-4<br>N1<br>NS2<br>PN2  |
| <b>Technical Data - Mechanical</b>   |  |   |
| Color  |  | Black   |
| Degree of protection / NEMA enclosure type                                       |  | IP66<br>Other   |
| Special features   |  | Additional terminal arrangement for sidewall drive with mounting bracket<br>For fitting to the mounting bracket when using N conductor or PE conductor terminals K50/1, K95/... or K150/... |
| <b>Design verification as per IEC/EN 61439</b>                                   |  |   |
| 10.2.2 Corrosion resistance  |  | Meets the product standard's requirements.  |
| 10.2.3.1 Verification of thermal stability of enclosures                         |  | Meets the product standard's requirements.  |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat       |  | Meets the product standard's requirements.  |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects |  | Meets the product standard's requirements.  |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                 |  | Meets the product standard's requirements.  |
| 10.2.5 Lifting   |  | Does not apply, since the entire switchgear needs to be evaluated.  |
| 10.2.6 Mechanical impact   |  | Does not apply, since the entire switchgear needs to be evaluated.  |
| 10.2.7 Inscriptions  |  | Meets the product standard's requirements.  |
| 10.3 Degree of protection of assemblies  |  | Does not apply, since the entire switchgear needs to be evaluated.  |
| 10.4 Clearances and creepage distances   |  | Meets the product standard's requirements.  |

|  |  |  |  |
|--|--|--|--|
| 10.5 Protection against electric shock                   |  |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.6 Incorporation of switching devices and components   |  |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.7 Internal electrical circuits and connections        |  |  | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors                 |  |  | Is the panel builder's responsibility.   |
| 10.9.2 Power-frequency electric strength                 |  |  | Is the panel builder's responsibility.   |
| 10.9.3 Impulse withstand voltage                         |  |  | Is the panel builder's responsibility.   |
| 10.9.4 Testing of enclosures made of insulating material |  |  | Is the panel builder's responsibility.   |
| 10.10 Temperature rise                                   |  |  | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating                               |  |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.12 Electromagnetic compatibility                      |  |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.13 Mechanical function                                |  |  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |

## Technical data ETIM 9.0

|  |  |  |       |
|--|--|--|-------|
| Low-voltage industrial components (EG000017) / Handle for power circuit breaker (EC000229)   |  |  |       |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Handle for switch devices (ecl@ss13-27-37-04-14 [AKF012019]) |  |  |       |
| With restart blockage  |  |  | No    |
| With key lock  |  |  | No    |
| Padlock locking  |  |  | No    |
| Colour   |  |  | Black |
| Suitable for emergency stop  |  |  | No    |
| With extension shaft   |  |  | No    |
| Suitable for power circuit breaker   |  |  | Yes   |
| Suitable for switch disconnecter   |  |  | Yes   |
| Degree of protection (NEMA)  |  |  | Other |