

Busbar, isolated, 80A, 2p

Part no. Z-GV-16/1P+N-2TE
271063
EL Number 1657114
(Norway)

| General specifications | | |
|---|--|--------------------------------------|
| Product name | | Eaton Distribution parts |
| Part no. | | Z-GV-16/1P+N-2TE |
| EAN | | 4015082710637 |
| Product Length/Depth | | 30 millimetre |
| Product height | | 14.9 millimetre |
| Product width | | 1016 millimetre |
| Product weight | | 0.47 kilogram |
| Compliances | | RoHS conform |
| Product Tradename | | None |
| Product Type | | Distribution parts |
| Product Sub Type | | None |
| Public Consumption | | Yes |
| Product Family Description | | ES-PMCC-PDC-Eaton Distribution parts |
| Globally Marketable | | Yes |
| Product Specification Details | | |
| Color | | Other |
| Cross section | | 16 mm ² |
| EL number | | 1657114 |
| Electric connection type | | Fork |
| Features | | Insulated Can be cut to size |
| Number of modular spacings | | 2 |
| Number of phases | | 2 |
| Number of poles | | Single-pole |
| Pitch dimensions | | 0 mm |
| Rated conditional short-circuit current (I _q) | | 0 kA |
| Rated operational voltage (U _e) - max | | 415 V |
| Rated short-time withstand current (I _{cw}) | | 0 kA |
| Rated surge voltage | | 0 kV |
| Rated uninterrupted current (I _u) | | 80 A |
| Suitable for | | Devices with N-busbar 8 devices |
| Suitable for number of devices | | 0 |

Technical data ETIM 9.0

| Low-voltage industrial components (EG000017) / Phase busbar (EC000215) | | |
|--|-----------------|------|
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss13-27-37-13-06 [ACN992016]) | | |
| Number of phases | | 2 |
| Number of poles | | 1 |
| Suitable for number of devices | | 0 |
| Module width | mm | 0 |
| Cross section | mm ² | 16 |
| Length | mm | 30 |
| Can be cut to size | | Yes |
| Width in number of modular spacings | | 2 |
| Rated permanent current I _u | A | 80 |
| Type of electric connection | | Fork |

| | | |
|--|----|-------|
| Insulated | | Yes |
| Rated surge voltage | kV | 0 |
| Conditioned rated short-circuit current Iq | kA | 0 |
| Max. rated operation voltage Ue | V | 415 |
| Rated short-time withstand current Icw | kA | 0 |
| Suitable for devices with N-conductor | | Yes |
| Suitable for devices with auxiliary switch | | No |
| Colour | | Other |