

**HALT/STOP-Button, RMQ-Titan, Mushroom-shaped, 38 mm, Non-illuminated, Turn-to-release function, Black, yellow, RAL 9005**

**Part no.**                    **M22S-PVT**  
**271499**

<b>General specifications</b>		
Product name		Eaton Moeller® series M22 Emergency stop/emergency switching off pushbutton
Part no.		M22S-PVT
EAN		4015082714994
Product Length/Depth		38 millimetre
Product height		70 millimetre
Product width		38 millimetre
Product weight		0.045 kilogram
Compliances		CE Marked
Certifications		CSA Std. C22.2 No. 14-05 CSA Std. C22.2 No. 94-91 EN 60947-5 IEC 60947-5 UL 508 VDE CSA Class No.: 3211-03 CSA File No.: 012528 IEC/EN 60947-5 CSA-C22.2 No. 94-91 VDE 0660 IEC/EN 60947 CSA UL Category Control No.: NKCR UL File No.: E29184 CE UL CSA-C22.2 No. 14-05 GL DNV LR
Product Tradename		M22
Product Type		Emergency stop/emergency switching off pushbutton
Product Sub Type		None
<b>Features &amp; Functions</b>		
Bezel color		Other
Base color		Yellow
Bezel material		Other
Color		Black
Design		Mushroom-shaped Classical
Illumination		Non-illuminated
RAL-number		9005
Unlocking method		Turn-release
<b>General information</b>		
Degree of protection		IP67/IP69K NEMA 4X, 13
Lifespan, mechanical		100,000 Operations
Opening diameter		22.5 mm
Operating frequency		600 Operations/h
Product category		RMQ-Titan
Size		Front dimensions: 35 mm
Type		Emergency stop pushbutton STOP pushbutton
<b>Ambient conditions, mechanical</b>		
Mounting position		As required
Shock resistance		Mechanical, According to IEC/EN 60068-2-27 50 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

<b>Climatic environmental conditions</b>		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Climatic proofing		Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
<b>Communication</b>		
Connection to SmartWire-DT		Yes With SWD-RMQ connections
<b>Actuator</b>		
Actuating force		50 N
Actuator color		Black
Actuator diameter		38 mm
Actuator function		Switching function latching Turn-to-release
<b>Contacts</b>		
Force for positive opening - min		0 N
<b>Design verification</b>		
Equipment heat dissipation, current-dependent Pvid		0 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
Rated operational current for specified heat dissipation (In)		0 A
Static heat dissipation, non-current-dependent Pvs		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		Not applicable.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Front element for mushroom push-button (EC001038)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for mushroom push-button actuators (ecl@ss13-27-37-12-12 [AKF030019])		
Colour button		Black
Construction type lens		Round
Diameter cap	mm	38
Hole diameter	mm	22.5
Width opening	mm	0
Height opening	mm	0

Degree of protection (IP)			IP67/IP69K
Degree of protection (NEMA)			4X, 13
Type of button			High
Suitable for illumination			No
With lighting			No
Supply voltage lamp		V	0
Switching function latching			Yes
Spring-return			No
With front ring			No
Material front ring			Other
Colour front ring			Other
Suitable for emergency stop			No
Unlocking method			Turn-release