

Main switch assembly kit, red



**Part no.**                    **NZM4-XHBR**  
**271842**

<b>General specifications</b>		
Product name		Eaton Moeller series NZM operating element
Part no.		NZM4-XHBR
EAN		4015082718428
Product Length/Depth		250 millimetre
Product height		165 millimetre
Product width		165 millimetre
Product weight		1.941 kilogram
Compliances		IEC UL/CSA RoHS conform
Certifications		CSA certified UL listed UL489 CSA (File No. 22086) UL (Category Control Number DIHS) IEC60947 UL (File No. E140305) CSA (Class No. 1437-01) CSA-C22.2 No. 5-09 CE marking
Product Tradename		NZM
Product Type		Accessories
Product Sub Type		Operating element
<b>Delivery program</b>		
Type		Accessory Main switch assembly kit
Features		Lockable With red door coupling rotary handle for use of switch as emergency switching off device to IEC/EN 60204-1, VDE 0113 part 1
Special features		External warning plate/designation label can be clipped on. For enhanced busbar tag shroud on the incomer side, please order IP2X protection against contact with a finger. Kit for use as a main switch
Frame		NZM4
Fitted with:		Extension shaft Door coupling rotary handle with rotary drive NZM...-XV4 extension shaft Black and yellow lightning symbol External warning plate/markings plate in German/English Padlock
Suitable for		Switch disconnecter Power circuit breaker Emergency stop
Used with		NZM4(-4) N(S)4(-4)
<b>Technical Data - Mechanical</b>		
Color		Black
Cover/door type		Door interlock not defeated in the locked OFF position. Door interlock on OFF with max. 3 padlocks After the door interlock is activated, must not be opened while on ON or TRIP. Must only be opened on OFF Door interlock can be modified such that it can be defeated from the outside using a screwdriver Door interlock can only be switched ON when the door is closed
Degree of protection / NEMA enclosure type		IP66 4X. 12
Locking facility		Lockable on the switch in the 0 position With door interlock Lockable on the 0 position on the handle using up to 3 padlocks
Special features		External warning plate/designation label can be clipped on. For enhanced busbar tag shroud on the incomer side, please order IP2X protection against contact with a finger. Kit for use as a main switch

Design verification as per IEC/EN 61439		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Handle for power circuit breaker (EC000229)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Handle for switch devices (ecl@ss13-27-37-04-14 [AKF012019])		
With restart blockage		No
With key lock		No
Padlock locking		Yes
Colour		Black
Suitable for emergency stop		Yes
With extension shaft		Yes
Suitable for power circuit breaker		Yes
Suitable for switch disconnecter		Yes
Degree of protection (NEMA)		4X, 12