


DATASHEET - DILM32-XSP(RDC60)



**Replacement coil, Tool-less plug connection, RDC 60: 48 - 60 V DC, DC,
For use with: DILM17, DILM25, DILM32, DILM38**



**Part no. DILM32-XSP(RDC60)
Catalog No. 281156
Alternate Catalog No. XTCERENCOILCWD**

Delivery program

| | | | |
|----------------------|--|--|--------------------------------------|
| Connection technique | | | Tool-less plug connection |
| Actuating voltage | | | RDC 60: 48 - 60 V DC |
| Voltage AC/DC | | | DC |
| For use with | | | DILM17 DILM25 DILM32 DILM38 |
| For use with | | | DILM17 - DILM38 |

Design verification as per IEC/EN 61439

| | | | |
|--|--|----|-----|
| Technical data for design verification | | | |
| Operating ambient temperature min. | | °C | -25 |
| Operating ambient temperature max. | | °C | 60 |

Technical data ETIM 7.0

| | | | |
|--|--|---|---------|
| Low-voltage industrial components (EG000017) / Coil for relay (EC001043) | | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Reel for contactor (ecl@ss10.0.1-27-37-10-12 [AKF021013]) | | | |
| Rated control supply voltage Us at AC 50HZ | | V | 0 - 0 |
| Rated control supply voltage Us at AC 60HZ | | V | 0 - 0 |
| Rated control supply voltage Us at DC | | V | 48 - 60 |
| Voltage type for actuating | | | DC |

Approvals

| | | | |
|--------------------------------------|--|--|---|
| Product Standards | | | IEC/EN 60947-4-1; UL 508; CSA-C22.2 No. 14-05; CE marking |
| UL File No. | | | E29096 |
| UL Category Control No. | | | NLDX |
| CSA File No. | | | 012528 |
| CSA Class No. | | | 2411-03, 3211-04 |
| North America Certification | | | UL listed, CSA certified |
| Specially designed for North America | | | No |

Assets (links)

Declaration of CE Conformity

00002870

Instruction Leaflets

IL03407036Z2018_04

Additional product information (links)

| | |
|--|---|
| IL03407036Z (AWA2100-2260) Coil exchange: DILM17 to DILM38 | |
| IL03407036Z (AWA2100-2260) Coil exchange: DILM17 to DILM38 | ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL03407036Z2018_04.pdf |
| Motor starters and "Special Purpose Ratings" for the North American market | http://www.eaton.eu/ecm/groups/public/@pub/@europe/@electrical/documents/content/pct_3258146.pdf |
| Switchgear of Power Factor Correction Systems | http://www.moeller.net/binary/ver_techpapers/ver934en.pdf |
| X-Start - Modern Switching Installations Efficiently Fitted and Wired Securely | http://www.moeller.net/binary/ver_techpapers/ver938en.pdf |
| Mirror Contacts for Highly-Reliable Information Relating to Safety-Related Control Functions | http://www.moeller.net/binary/ver_techpapers/ver944en.pdf |

| | |
|--|---|
| Effect of the Cable Capacitance of Long Control Cables on the Actuation of Contactors | http://www.moeller.net/binary/ver_techpapers/ver949en.pdf |
| Switchgear for Luminaires | http://www.moeller.net/binary/ver_techpapers/ver955en.pdf |
| Standard Compliant and Functionally Safe Engineering Design with Mechanical Auxiliary Contacts | http://www.moeller.net/binary/ver_techpapers/ver956en.pdf |
| The Interaction of Contactors with PLCs | http://www.moeller.net/binary/ver_techpapers/ver957en.pdf |
| Busbar Component Adapters for modern Industrial control panels | http://www.moeller.net/binary/ver_techpapers/ver960en.pdf |