

Surface-mount service distribution board base frame HxW = 1560 x 800 mm



Part no. BP-MF-800/15

286667

EL Number (Norway)

2456025

| General specifications | | |
|---|--|---|
| Product name | | Eaton xEnergy Basic frame |
| Part no. | | BP-MF-800/15 |
| EAN | | 4015082866679 |
| Product Length/Depth | | 50 millimetre |
| Product height | | 1580 millimetre |
| Product width | | 815 millimetre |
| Product weight | | 17 kilogram |
| Compliances | | RoHS conform |
| Product Tradename | | xEnergy Basic |
| Product Type | | Accessories |
| Product Sub Type | | Frame |
| Delivery program | | |
| Type | | Additional equipment |
| Color | | Stainless steel |
| Technical Data - Mechanical | | |
| Surface finishing | | Galvanized |
| Mounting method | | Surface mounting Wall fastening |
| Material | | Sheet steel Steel |
| Degree of protection | | IP30 IK08 (impact resistance) Other |
| Number of connector holes | | 0 |
| Number of covers/doors | | 0 |
| Number of locks | | 0 |
| Permissible load of the door(s) according to IEC 62208 - max | | 0 N |
| Permissible load of the enclosure according to IEC 62208 - max | | 0 N |
| Permissible load of the mounting plate according to IEC 62208 - max | | 0 N |
| Grade material | | Sheet steel |
| Installation type | | Floor installation possible |
| Suitable for width | | 800 mm |
| Temperature-rise verification as per IEC 60890 | | |
| Thermal dissipation (Delta T = 20 K) according to IEC/TR 60890 | | 0 W |
| Additional information | | |
| Features | | Connectable EMC-version |
| Functions | | Additional equipment |
| RAL-number | | 0 |
| Suitable for | | Metrical mounting |

Technical data ETIM 9.0

| | | | |
|--|--|----|------|
| Cabinet enclosures (EG000011) / Enclosure/cabinet (empty) (EC000261) | | | |
| Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Electrical cabinet (empty) / Electrical cabinet, Empty enclosures (ecl@ss13-27-18-01-01 [AGZ056021]) | | | |
| Width | | mm | 815 |
| Height | | mm | 1580 |
| Depth | | mm | 50 |

| | | | |
|--|--|---|-----------------|
| Material | | | Steel |
| Material quality | | | Other |
| Surface finishing | | | Galvanized |
| Colour | | | Stainless steel |
| RAL-number | | | 0 |
| Freestanding | | | No |
| Floor standing wall model | | | No |
| Suitable for wall mounting | | | Yes |
| Corner model | | | No |
| Intermediate mounting | | | No |
| Couplable | | | Yes |
| With mounting plate | | | No |
| Mounting plate depth-adjustable | | | No |
| Suitable for wall built-in | | | No |
| Pole fastening | | | No |
| With door | | | No |
| Number of doors | | | 0 |
| With glazed door | | | No |
| With ventilation door | | | No |
| With rear door | | | No |
| Number of locks | | | 0 |
| With cover | | | No |
| Transparent cover | | | No |
| Suitable for metrical mounting | | | Yes |
| Suitable for outdoor set-up | | | No |
| Pitched roof | | | No |
| Number of connector holes | | | 0 |
| Pre-stamping | | | No |
| EMC-version | | | Yes |
| Impact strength | | | IK08 |
| Degree of protection (IP) | | | IP30 |
| Degree of protection (NEMA) | | | Other |
| Thermal dissipation (Delta T = 20 K) according to IEC/TR 60890 | | W | 0 |
| Max. permissible load of the enclosure according to IEC 62208 | | N | 0 |
| Max. permissible load of the door(s) according to IEC 62208 | | N | 0 |
| Max. permissible load of the mounting plate according to IEC 62208 | | N | 0 |