

**Auxiliary contact, 2early N/O, operates as an early-make contact,
connection right**

**Part no. NZM1-XHIVR
292195**

General specifications		
Product name		Eaton Moeller series NZM auxiliary contact
Part no.		NZM1-XHIVR
EAN		4015082921958
Product Length/Depth		37 millimetre
Product height		66 millimetre
Product width		32 millimetre
Product weight		0.038 kilogram
Compliances		RoHS conform
Certifications		CSA (File No. 22086) UL (Category Control Number DIHS) CSA certified UL (File No. E140305) UL listed IEC60947 CE marking CSA (Class No. 1437-01) CSA-C22.2 No. 5-09 UL489
Product Tradename		NZM
Product Type		Accessories
Product Sub Type		Auxiliary contact
Delivery program		
Special features		C300/R300 (auxiliary contacts, UL/CSA, pilot duty)
Used with		FAZ-B6 (max. miniature circuit breaker)
Technical Data - Electrical		
Voltage rating at DC		220 V DC
Voltage rating at AC		500 V AC
Rated operational current		2.5 A at 240 V AC (UL/CSA) 1 A at 250 V DC (UL/CSA)
Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V		4 A
Conventional thermal current Ith of auxiliary contacts		4 A
Fuse short-circuit protection - max		10 A gG/gL
Technical Data - Mechanical		
Mounting Method		Other
Number of contacts (change-over contacts)		0
Number of contacts (normally closed contacts)		0
Number of contacts (normally open contacts)		2
Connection type		Screw
Lamp holder		None
Special features		C300/R300 (auxiliary contacts, UL/CSA, pilot duty)
Technical Data - Mechanical - Terminals		
Terminal capacity (solid/flexible conductor)		18 - 14 AWG (1x) at auxiliary contacts 0.75 mm ² - 2.5 mm ² (2x) at auxiliary contacts with ferrule 18 - 14 AWG (2x) at auxiliary contacts 0.75 mm ² - 2.5 mm ² (1x) at auxiliary contacts with ferrule
Design verification as per IEC/EN 61439		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.

10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
Additional information			
Model			Integrable

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ecI@ss13-27-37-13-02 [AKN342018])			
Number of contacts as change-over contact			0
Number of contacts as normally open contact			2
Number of contacts as normally closed contact			0
Number of fault-signal switches			
Rated operation current Ie at AC-15, 230 V		A	4
Type of electric connection			Screw connection
Model			Integrable
Mounting method			Other
Lamp holder			None