



Eaton 9PX 5000i HotSwap

Part no.

Eaton 9PX 5000i HotSwap

Catalog No.

9PX5KIBP

Delivery program

Product range		UPS
---------------	--	-----

Technical data ETIM 7.0

Data and telecommunication (EG000037) / UPS (EC000382)		
Electric engineering, automation, process control engineering / Power supply devices / No-break power supply (complete) / No-break power supply (complete, unspecified) (ecl@ss10.0.1-27-04-06-90 [BAB258012])		
Input voltage	V	100 - 276
Primary frequency	Hz	40 - 70
Number of phases primary		1
Output voltage	V	200 - 240
Secondary frequency	Hz	50 - 60
Output effective power	W	4500
Output apparent power	VA	5000
Type of interface		Other
Number of phases secondary		1
SNMP		Yes
Voltage type		AC
Height	mm	440
Width	mm	130
Depth	mm	685
Transition time for full load	min	3.5
Weight	kg	48
Network-management		Yes
USV- technology		Online
Construction type		Free standing model
Max. voltage distortion output (linear load)	%	2
Output power factor		0.9
Overall efficiency	%	94
Efficiency in eco-mode	%	98
Potential free switch contact		Yes
Auto shut down function		Yes
Input connection		Fixed connection
Number of output connections C13		3
Number of output connections C19		2
Number of output connections with protective contact (SCHUKO)		0
Number of output connections fixed connection		1