

Maintenance key, handle, for P3

Part no. **KNK-P3**
000649

| General specifications | |
|--|--|
| Product name | Eaton Moeller® series Accessory Maintenance key |
| Part no. | KNK-P3 |
| EAN | 4015080006497 |
| Product Length/Depth | 75 millimetre |
| Product height | 60 millimetre |
| Product width | 40 millimetre |
| Product weight | 0.028 kilogram |
| Certifications | UL/CSA certification not required |
| Product Tradename | None |
| Product Type | Accessory |
| Product Sub Type | Maintenance key |
| Catalog Notes | Special devices for electricians: Interlocked main switches can be switched on and off for repairs with the maintenance key while the door is open (as per IEC/EN 60204-1) |
| General information | |
| Accessory/spare part type | Accessory |
| Type | Maintenance key |
| Used with | T5-.../V... T5B-.../V... |
| Climatic environmental conditions | |
| Ambient operating temperature - min | -25 °C |
| Ambient operating temperature - max | 50 °C |
| Design verification | |
| Equipment heat dissipation, current-dependent P _{vid} | 0 W |
| Heat dissipation capacity P _{diss} | 0 W |
| Heat dissipation per pole, current-dependent P _{vid} | 0 W |
| Rated operational current for specified heat dissipation (I _n) | 0 A |
| Static heat dissipation, non-current-dependent P _{vs} | 0 W |
| 10.2.2 Corrosion resistance | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | Meets the product standard's requirements. |
| 10.2.5 Lifting | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | Is the panel builder's responsibility. |
| 10.10 Temperature rise | Not applicable. |
| 10.11 Short-circuit rating | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |

| | | | |
|-------------------------------------|--|--|--|
| 10.12 Electromagnetic compatibility | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 9.0

| | | | |
|--|--|--|-------|
| Low-voltage industrial components (EG000017) / Accessories/spare parts for command devices (EC002024) | | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Command and alarm device (accessories) (ecl@ss13-27-37-12-92 [AC0037015]) | | | |
| Type of electrical accessory/spare part | | | Other |
| Type of mechanical accessory/spare part | | | Key |
| Accessory | | | Yes |
| Spare part | | | No |