

Emergency-Stop label, Yellow, black lettering, Round, 60 mm, de, en, fr, it,
Front dimensions 25 × 25 mm

Part no. **SRT1**
 058873

| General specifications | | |
|--|--|--|
| Product name | | Eaton Moeller® series RMQ16 Accessory Emergency-Stop label |
| Part no. | | SRT1 |
| EAN | | 4015080588733 |
| Product Length/Depth | | 60 millimetre |
| Product height | | 1 millimetre |
| Product width | | 60 millimetre |
| Product weight | | 0.006 kilogram |
| Certifications | | UL/CSA certification not required |
| Product Tradename | | RMQ16 |
| Product Type | | Accessory |
| Product Sub Type | | Emergency-Stop label |
| Features & Functions | | |
| Color | | Yellow |
| Inscription | | Other |
| Language | | Several |
| Shape | | Round |
| General information | | |
| Size | | 25 × 25 mm |
| Climatic environmental conditions | | |
| Ambient operating temperature - min | | -25 °C |
| Ambient operating temperature - max | | 60 °C |
| Communication | | |
| Connection to SmartWire-DT | | No |
| Design verification | | |
| Equipment heat dissipation, current-dependent P _{vid} | | 0 W |
| Heat dissipation capacity P _{diss} | | 0 W |
| Heat dissipation per pole, current-dependent P _{vid} | | 0 W |
| Rated operational current for specified heat dissipation (I _n) | | 0 A |
| Static heat dissipation, non-current-dependent P _{vs} | | 0 W |
| 10.2.2 Corrosion resistance | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | Please enquire |
| 10.2.5 Lifting | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | Is the panel builder's responsibility. |

| | | | |
|-------------------------------------|--|--|--|
| 10.10 Temperature rise | | | Not applicable. |
| 10.11 Short-circuit rating | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 9.0

| | | | |
|--|--|----|---------|
| Low-voltage industrial components (EG000017) / Text plate for command devices (EC000624) | | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Identification plate for command devices (ecl@ss13-27-37-12-25 [AKF043019]) | | | |
| Literal imprint | | | Other |
| Language of the imprint | | | Several |
| Imprint ISO symbols | | | None |
| Colour | | | Yellow |
| Shape | | | Round |
| Width | | mm | 60 |
| Height | | mm | 1 |
| Outer diameter | | mm | 60 |