

Busbar support, for CI enclosure 375mm, hxD=20x5(10, 15)mm



Part no. SH0635/4
060620
EL Number 2502251
(Norway)

General specifications		
Product name		Eaton xEnergy Safety Ci busbar enclosure accessory
Part no.		SH0635/4
EAN		4015080606208
Product Length/Depth		20 millimetre
Product height		100 millimetre
Product width		300 millimetre
Product weight		0.243 kilogram
Compliances		RoHS conform
Product Tradename		xEnergy Safety Ci
Product Type		Accessories
Product Sub Type		Busbar enclosure accessory
Delivery program		
Type		Accessory for busbar enclosures Prepared enclosures xEnergy Safety Ci
Accessory/spare part type		Busbar support
Number of poles		Five-pole
Technical Data - Electrical		
Current rating - max		630 A
Rated operation current (Ie)		630 A 250 A 400 A
Technical Data - Mechanical		
Distance between busbar centers		50 mm
Busbar distance		50 mm
Additional information		
Functions		For use between two enclosures Prepared enclosure
Special features		Component mounting possible on busbar Interval between busbar supports max. 375 mm
Suitable for		Use between two enclosures
Used with		CI43... L1, L2, L3, PE, N, PEN: 20 x 5 CI44... CI48... CI45... L1, L2, L3: 20 x 10 + 20 x 5; PE, N, PEN: 20 x 10 L1, L2, L3: 20 x 10; PE, N, PEN: 20 x 5 xEnergy Safety Ci Prepared enclosures Accessory for busbar enclosures

Technical data ETIM 9.0

Energy distribution systems (EG000015) / Busbar support (EC001166)		
Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Busbar carrier (ec@ss13-27-40-06-07 [AC0377016])		
Number of poles		5
Max. rated current	A	630
Busbar distance	mm	50