

Amplifier module, for separate mounting

Part no. **ETS4-VS3**
083094

General specifications	
Product name	Eaton Moeller® series amplifier module
Part no.	ETS4-VS3
EAN	4015080830948
Product Length/Depth	103 millimetre
Product height	83 millimetre
Product width	23 millimetre
Product weight	0.1 kilogram
Certifications	UL File No.: E29184 UL UL Listed CSA file No. 012528 CSA-C22.2 No. 14-05 CSA UL 508 UL Category Control No.: NKCR CSA Class No.: 2411-03, 3211-04 IEC/EN 60947-4-1 CSA certified VDE 0660 IEC/EN 60947 CE marking
Product Tradename	None
Product Type	Accessory
Product Sub Type	Amplifier module
Features & Functions	
Fitted with:	LED indication
General information	
Application	Contactors relays
Mounting method	DIN rail
Voltage type	DC
Electrical rating	
Rated operational current (Ie)	2 A
Rated operational current (Ie) at AC-15, 380 V, 400 V, 415 V	2 A
Magnet system	
Rated control supply voltage (Us) at AC, 50 Hz - min	0 V
Rated control supply voltage (Us) at AC, 50 Hz - max	0 V
Rated control supply voltage (Us) at AC, 60 Hz - min	0 V
Rated control supply voltage (Us) at AC, 60 Hz - max	0 V
Rated control supply voltage (Us) at DC - min	24 V
Rated control supply voltage (Us) at DC - max	24 V
Contacts	
Control circuit reliability	< 2 λ, < 1 failure at 100,000,000 Operations (at U# = 24 V DC, Umin = 17 V, Imin = 5.4 mA)
Number of auxiliary contacts (normally closed contacts)	1
Number of auxiliary contacts (normally open contacts)	1
Design verification	
Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdis	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Contactor relay (EC000196)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Contactor relay (ecl@ss13-27-37-10-01 [AAB716019])		
Rated control supply voltage AC 50 Hz	V	0 - 0
Rated control supply voltage AC 60 Hz	V	0 - 0
Rated control supply voltage DC	V	24 - 24
Voltage type for actuating		DC
Rated operation current	A	2
Rated operation current I _e , 400 V	A	2
Mounting method		DIN rail
With LED indication		Yes
Suitable for manual operation		No
Interface		No
Number of auxiliary contacts as normally closed contact		1
Number of auxiliary contacts as normally open contact		1
Number of auxiliary contacts as normally closed contact, delayed switching		0
Number of auxiliary contacts as normally open contact, leading		0
Number of auxiliary contacts as change-over contact		0
Operating voltage AC 50 Hz	V	220 - 440
Operating voltage AC 60 Hz	V	220 - 440
Operating voltage DC	V	0 - 0
Voltage type (operating voltage)		AC
Rated switch current	A	2
Connection type auxiliary circuit		Screw connection
Width	mm	23
Height	mm	83
Depth	mm	103