

Pushbutton, white, momentary

Part no. Q25D-WS
086808

| General specifications | | |
|--|--|---|
| Product name | | Eaton Moeller® series RMQ16 Pushbutton |
| Part no. | | Q25D-WS |
| EAN | | 4015080868088 |
| Product Length/Depth | | 50 millimetre |
| Product height | | 25 millimetre |
| Product width | | 25 millimetre |
| Product weight | | 0.008 kilogram |
| Certifications | | UL VDE 0660 CSA-C22.2 No. 14-05 IEC/EN 60947 UL Category Control No.: NKCR CE CSA File No.: 46552 UL File No.: E29184 CSA CSA Class No.: 3211-03 IEC/EN 60947-5 UL 508 |
| Product Tradename | | RMQ16 |
| Product Type | | Pushbutton |
| Product Sub Type | | None |
| Features & Functions | | |
| Bezel color | | Black |
| Bezel material | | Plastic |
| Design | | Flat |
| Fitted with: | | Front ring |
| Inscription | | Blank |
| General information | | |
| Degree of protection | | IP65 NEMA 1 |
| Degree of protection (front side) | | NEMA 1 IP65 |
| Lifespan, mechanical | | 3,000,000 Operations |
| Opening diameter | | 16 mm |
| Operating frequency | | 3600 Operations/h |
| Product category | | RMQ16 |
| Size | | Front dimensions: 25 x 25 mm |
| Type | | Pushbutton actuator |
| Ambient conditions, mechanical | | |
| Mounting position | | As required |
| Shock resistance | | 40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27 |
| Climatic environmental conditions | | |
| Ambient operating temperature - min | | -25 °C |
| Ambient operating temperature - max | | 60 °C |
| Ambient operating temperature (enclosed) - min | | 25 °C |
| Ambient operating temperature (enclosed) - max | | 40 °C |
| Climatic proofing | | Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30 |
| Actuator | | |
| Actuating force | | 4 N |
| Actuator color | | White |

| | | |
|--|--|--|
| Actuator function | | Spring-return Momentary |
| Communication | | |
| Connection to SmartWire-DT | | No |
| Design verification | | |
| Equipment heat dissipation, current-dependent Pvid | | 0 W |
| Heat dissipation capacity Pdis | | 0 W |
| Heat dissipation per pole, current-dependent Pvid | | 0 W |
| Rated operational current for specified heat dissipation (In) | | 0 A |
| Static heat dissipation, non-current-dependent Pvs | | 0 W |
| 10.2.2 Corrosion resistance | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | Please enquire |
| 10.2.5 Lifting | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | Not applicable. |
| 10.11 Short-circuit rating | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 9.0

| | | |
|---|----|---------|
| Low-voltage industrial components (EG000017) / Front element for push button (EC000221) | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for push-button actuators (ecl@ss13-27-37-12-10 [AKF028019]) | | |
| Colour button | | White |
| Number of command positions | | 1 |
| Construction type lens | | Square |
| Hole diameter | mm | 16 |
| Width opening | mm | 0 |
| Height opening | mm | 0 |
| Type of button | | Flat |
| Suitable for illumination | | No |
| With protective cover | | No |
| Labelled | | No |
| Switching function latching | | No |
| Spring-return | | Yes |
| With front ring | | Yes |
| Material front ring | | Plastic |
| Colour front ring | | Black |
| Degree of protection (IP), front side | | IP65 |
| Degree of protection (NEMA), front side | | 1 |

