

Flange, knockout, 18x M16, 4x M20, HxWxD=116x250x23mm



Part no. FL3-1
088425
EL Number 4132065
(Norway)

General specifications			
Product name			Eaton xEnergy Safety Ci flange plate
Part no.			FL3-1
EAN			4015080884255
Product Length/Depth			115 millimetre
Product height			23 millimetre
Product width			205 millimetre
Product weight			0.18 kilogram
Compliances			RoHS conform
Product Tradename			xEnergy Safety Ci
Product Type			Accessories
Product Sub Type			Flange plate
Delivery program			
Type			Accessory for basic enclosures Basic enclosure xEnergy Safety Ci
Model			Cable screw gland
Accessory/spare part type			Flanges
Technical Data - Mechanical			
Shape			Straight
Unit type			Modular system
Surface protection			Untreated
Material			Plastic
Degree of protection			Other
Number of connector holes			0
Cable entry type			4 x M20 18 x M16
Thickness			4 mm
Thread type			Metric
Suitable for cable diameter - min			0 mm
Suitable for cable diameter - max			0 mm
Suitable for nominal thread (PG) - min			16
Suitable for nominal thread (PG) - max			20
Additional information			
Features			Pre-stamping
Special features			Sponge-rubber, captive gasket Quick mounting using wedge-lock fasteners (included as standard)
Used with			250 mm (enclosure dimensions) xEnergy Safety Ci Basic enclosure Accessory for basic enclosures

Technical data ETIM 9.0

Distribution boards (EG000023) / Gland plate for enclosure/cabinet (EC000211)			
Electric engineering, automation, process control engineering / Electrical installation, device / Electrical distribution system (including small distribution board) / Gland plate for small distribution boards/switchgear cabinets (ecl@ss13-27-14-24-21 [ADI315012])			
Model			Cable screw gland
Type			Straight
Width		mm	205
Height		mm	23
Thickness		mm	4
Material			Plastic

Surface protection			Untreated
Degree of protection (NEMA)			Other
Pre-stamping			Yes
Number of connector holes			0
Suitable for cable diameter		mm	0 - 0
Thread type			Metric
Suitable for nominal thread metric/PG			16 - 20
Gland plate type according to SEN 280901			