

Part no. **Q18LT-RT/WB**
088537

| General specifications | |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product name | Eaton Moeller® series RMQ16 Illuminated pushbutton actuator |
| Part no. | Q18LT-RT/WB |
| EAN | 4015080885375 |
| Product Length/Depth | 59 millimetre |
| Product height | 18 millimetre |
| Product width | 18 millimetre |
| Product weight | 0.009 kilogram |
| Certifications | CE CSA-C22.2 No. 14-05 UL Category Control No.: NKCR CSA File No.: 46552 CSA IEC/EN 60947-5 UL UL File No.: E29184 UL 508 CSA Class No.: 3211-03 IEC/EN 60947 |
| Product Tradename | RMQ16 |
| Product Type | Illuminated pushbutton actuator |
| Product Sub Type | None |
| Catalog Notes | Use of insulated ferrule ISH 2,8 > 24 V AC/DC recommended Use of insulated ferrule ISH 2,8 > 50 V AC or 120 V DC is mandatory, even on unused blade terminals |
| Features & Functions | |
| Bezel color | Black |
| Bezel material | Plastic |
| Design | Flat |
| Fitted with: | Filament bulb (24 V) |
| Inscription | Blank |
| General information | |
| Degree of protection | IP65 NEMA 1 |
| Degree of protection (front side) | IP65 NEMA 1 |
| Lifespan, mechanical | 3,000,000 Operations |
| Opening diameter | 16 mm |
| Operating frequency | 3600 Operations/h |
| Overvoltage category | III |
| Pollution degree | 3 |
| Product category | RMQ16 |
| Size | Front dimensions: 18 x 18 mm |
| Rated impulse withstand voltage (Uimp) | 800 V AC |
| Suitable for | Illumination |
| Terminal size | 2.8 x 0.8 mm to DIN 46244, Blade terminal 2.8 x 0.8 mm to DIN 46247 and IEC 60760, Fast-on connectors |
| Type | Illuminated pushbutton actuator |
| Ambient conditions, mechanical | |
| Mounting position | As required |
| Shock resistance | 40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27 |
| Climatic environmental conditions | |
| Ambient operating temperature - min | -25 °C |
| Ambient operating temperature - max | 60 °C |

| | | |
|----------------------------------------------------------------------------------|--|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ambient operating temperature (enclosed) - min | | 25 °C |
| Ambient operating temperature (enclosed) - max | | 40 °C |
| Climatic proofing | | Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78 |
| Electrical rating | | |
| Rated insulation voltage (Ui) | | 250 V |
| Rated operational voltage (Ue) at AC - max | | 24 V |
| Actuator | | |
| Actuating force | | 4 N |
| Actuator color | | Red |
| Actuator function | | Momentary Spring-return |
| Contacts | | |
| Control circuit reliability | | 1 failure per 5,000,000 switching operations (statistically determined, at 5 V DC/1 mA) 1 failure per 10,000,000 switching operations (Statistically determined, at 24 V DC/5 mA) |
| Communication | | |
| Connection to SmartWire-DT | | No |
| Design verification | | |
| Equipment heat dissipation, current-dependent Pvid | | 0 W |
| Heat dissipation capacity Pdis | | 0 W |
| Heat dissipation per pole, current-dependent Pvid | | 0 W |
| Rated operational current for specified heat dissipation (In) | | 0 A |
| Static heat dissipation, non-current-dependent Pvs | | 1 W |
| 10.2.2 Corrosion resistance | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | Please enquire |
| 10.2.5 Lifting | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 9.0

| | | |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--------|
| Low-voltage industrial components (EG000017) / Front element for push button (EC000221) | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for push-button actuators (ecl@ss13-27-37-12-10 [AKF028019]) | | |
| Colour button | | Red |
| Number of command positions | | 1 |
| Construction type lens | | Square |

| | | |
|-----------------------------------------|----|---------|
| Hole diameter | mm | 16 |
| Width opening | mm | 0 |
| Height opening | mm | 0 |
| Type of button | | Flat |
| Suitable for illumination | | Yes |
| With protective cover | | No |
| Labelled | | No |
| Switching function latching | | No |
| Spring-return | | Yes |
| With front ring | | No |
| Material front ring | | Plastic |
| Colour front ring | | Black |
| Degree of protection (IP), front side | | IP65 |
| Degree of protection (NEMA), front side | | 1 |