Door, transparent smoky gray, for cap Cl43

Powering Business Worldwide

T-C143 Part no. 096206 **EL Number** 2502350

(Norway)

(INULVVAY)	
General specifications	
Product name	Eaton xEnergy Safety Ci door
Part no.	T-Cl43
EAN	4015080962069
Product Length/Depth	40 millimetre
Product height	250 millimetre
Product width	375 millimetre
Product weight	0.552 kilogram
Compliances	RoHS conform
Product Tradename	xEnergy Safety Ci
Product Type	Accessories
Product Sub Type	Door
Delivery program	
Туре	Accessory for basic enclosures Basic enclosure xEnergy Safety Ci
Model	Protective door
Accessory/spare part type	Doors
Color	Other
Technical Data - Mechanical	
Unit type	Modular system
Surface finishing	Untreated
Material	Plastic
Degree of protection	Other IP65
Cover/door type	Transparent, smoky gray
Additional information	
Features	Version as glazed door
Special features	Adhesive film for marking the cutout Delivery with fixing screws For increasing the mounting depth by 13.5 mm and the exterior height by 16 mm Opening angle 180° Door hinges can be subsequently changed to left, right, top or bottom.
Used with	CI45, DCI45 CI43, DCI43 Basic enclosure Accessory for basic enclosures xEnergy Safety Ci

Technical data ETIM 9.0

Cabinet enclosures (EG000011) / Door/operating panel (enclosure/cabinet) (EC000747)

Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Door (electrical cabinet) / Door/operating panel (enclosure) (ecl@ss13-27-18-22-04

[ACN614016])				
Model		Protective door		
Version as glazed door		Yes		
Version as door for disconnecting switch interlocking		No		
Width	mm	375		
Height	mm	250		
Depth	mm	40		
EMC-version		No		
Material		Plastic		
Surface finishing		Untreated		

Colour	Other
Degree of protection (IP)	Other
Degree of protection (NEMA)	Other