

Molded Case Switch, 3p, 250A



Part no. **NS2-250-NA**
102686
EL Number **4315510**
(Norway)

| General specifications | | |
|---|--|---|
| Product name | | Eaton Moeller series NZM - Molded Case Circuit Breaker |
| Part no. | | NS2-250-NA |
| EAN | | 4015081025466 |
| Product Length/Depth | | 142 millimetre |
| Product height | | 185 millimetre |
| Product width | | 105 millimetre |
| Product weight | | 2.398 kilogram |
| Compliances | | RoHS conform |
| Certifications | | CSA certified UL (Category Control Number WJAZ) UL listed UL 489 CSA (File No. 22086) IEC 60947-2 CSA-C22.2 No. 5-09 IEC CE marking UL (File No. E148671) UL/CSA Specially designed for North America CSA (Class No. 4652-06) |
| Product Tradename | | NZM |
| Product Type | | Molded Case Circuit Breaker |
| Product Sub Type | | None |
| Delivery program | | |
| Application | | Branch circuits, feeder circuits |
| Type | | Switch-disconnector |
| Circuit breaker frame type | | N2 |
| Number of poles | | Three-pole |
| Amperage Rating | | 250 A |
| Features | | Motor drive optional Protection unit |
| Special features | | IEC/EN 60947-2: circuit breakers without overcurrent (CBI-X) with main switch characteristics and isolating characteristics to IEC/EN 60204. Rated current = rated uninterrupted current: 250 A |
| Technical Data - Electrical | | |
| Voltage rating | | 690 V - 690 V |
| Rated operating voltage Ue (UL) - max | | 600 Y / 347 V |
| Rated insulation voltage (Ui) | | 1000 V AC |
| Rated impulse withstand voltage (Uimp) at auxiliary contacts | | 6000 V |
| Rated impulse withstand voltage (Uimp) at main contacts | | 8000 V |
| Current rating (Iu) (UL 489 csa 22.2 no. 5.1) | | 250 A |
| Rated current (Iu) | | 250 A |
| Instantaneous current setting (Ii) - min | | 2500 A |
| Instantaneous current setting (Ii) - max | | 2500 A |
| Overload current setting (Ir) - min | | 0 A |
| Overload current setting (Ir) - max | | 0 A |
| Short delay current setting (Isd) - min | | 0 A |
| Short delay current setting (Isd) - max | | 0 A |
| Short-circuit release non-delayed setting - min | | 2500 A |
| Short-circuit release non-delayed setting - max | | 2500 A |
| Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 230 V, 50/60 Hz | | 150 kA |
| Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 400/415 V, 50/60 Hz | | 150 kA |

| | | |
|---|--|---|
| Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 440 V, 50/60 Hz | | 130 kA |
| Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 525 V, 50/60 Hz | | 37.5 kA |
| Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 690 V, 50/60 Hz | | 5 kA |
| Rated short-circuit making capacity Icm at 240 V, 50/60 Hz | | 330 kA |
| Rated short-circuit making capacity Icm at 400/415 V, 50/60 Hz | | 330 kA |
| Rated short-circuit making capacity Icm at 440 V, 50/60 Hz | | 286 kA |
| Rated short-circuit making capacity Icm at 525 V, 50/60 Hz | | 105 kA |
| Rated short-circuit making capacity Icm at 690 V, 50/60 Hz | | 53 kA |
| Short-circuit total breaktime | | < 10 ms |
| Electrical connection type of main circuit | | Screw connection |
| Number of operations per hour - max | | 120 |
| Handle type | | Rocker lever |
| Overvoltage category | | III |
| Pollution degree | | 3 |
| Lifespan, electrical | | 6500 operations at 400 V AC-3 7500 operations at 690 V AC-1 10000 operations at 415 V AC-1 5000 operations at 690 V AC-3 6500 operations at 415 V AC-3 10000 operations at 400 V AC-1 |
| Direction of incoming supply | | As required |
| Technical Data - Mechanical | | |
| Mounting Method | | Fixed DIN rail (top hat rail) mounting optional Built-in device fixed built-in technique |
| Degree of protection | | In the area of the HMI devices: IP20 (basic protection type) IP20 |
| Degree of protection (IP), front side | | IP40 (with insulating surround) IP66 (with door coupling rotary handle) |
| Degree of protection (terminations) | | IP10 (tunnel terminal) IP00 (terminations, phase isolator and band terminal) |
| Number of auxiliary contacts (change-over contacts) | | 0 |
| Number of auxiliary contacts (normally closed contacts) | | 0 |
| Number of auxiliary contacts (normally open contacts) | | 0 |
| Position of connection for main current circuit | | Front side |
| Switch positions | | I, +, 0 |
| Special features | | IEC/EN 60947-2: circuit breakers without overcurrent (CBI-X) with main switch characteristics and isolating characteristics to IEC/EN 60204. Rated current = rated uninterrupted current: 250 A |
| Lifespan, mechanical | | 20000 operations |
| Technical Data - Mechanical - Terminals | | |
| Standard terminals | | Screw terminal |
| Optional terminals | | Box terminal. Connection on rear. Tunnel terminal |
| Terminal capacity (aluminum solid conductor/cable) | | 10 mm ² - 16 mm ² (2x) direct at switch rear-side connection 16 mm ² (1x) at tunnel terminal 10 mm ² - 16 mm ² (1x) direct at switch rear-side connection |
| Terminal capacity (aluminum stranded conductor/cable) | | 25 mm ² - 185 mm ² (1x) at 1-hole tunnel terminal 25 mm ² - 35 mm ² (2x) direct at switch rear-side connection 25 mm ² - 35 mm ² (1x) direct at switch rear-side connection |
| Terminal capacity (copper busbar) | | M8 at rear-side screw connection Max. 24 mm x 8 mm direct at switch rear-side connection NA: M8 at rear-side screw connection Min. 16 mm x 5 mm direct at switch rear-side connection NA: min. 16 mm x 5 mm direct at switch rear-side connection NA: max. 20 mm x 5 mm direct at switch rear-side connection |
| Terminal capacity (copper solid conductor/cable) | | 10 mm ² - 16 mm ² (1x) at box terminal NA: 12 - 6 AWG (1x) at box terminal 10 mm ² - 16 mm ² (1x) direct at switch rear-side connection 4 mm ² - 16 mm ² (2x) direct at switch rear-side connection 16 mm ² (1x) at tunnel terminal 6 mm ² - 16 mm ² (2x) at box terminal NA: 6 AWG (1x) at tunnel terminal NA: 12 - 6 AWG (1x) direct at switch rear-side connection |
| Terminal capacity (copper stranded conductor/cable) | | 25 mm ² - 185 mm ² (1x) at box terminal 25 mm ² - 70 mm ² (2x) direct at switch rear-side connection 25 mm ² - 70 mm ² (2x) at box terminal 25 mm ² - 185 mm ² (1x) at 1-hole tunnel terminal NA: 4 - 350 AWG/kcmil (1x) at 1-hole tunnel terminal 25 mm ² - 185 mm ² (1x) direct at switch rear-side connection |

| | | |
|--|--|--|
| Terminal capacity (copper strip) | | NA: 4 - 350 AWG/kcmil (1x) at box terminal Max. 10 segments of 24 mm x 0.8 mm at rear-side connection (punched) Min. 2 segments of 16 mm x 0.8 mm at rear-side connection (punched) NA: min. 2 segments of 16 mm x 0.8 mm at rear-side connection (punched) Max. 8 segments of 15.5 mm x 0.8 mm (2x) at terminal box Min. 2 segments of 9 mm x 0.8 mm at box terminal NA: max. 10 segments of 16 mm x 0.8 mm at rear-side connection (punched) Max. 10 segments of 16 mm x 0.8 mm at box terminal |
| Design verification as per IEC/EN 61439 - technical data | | |
| Rated operational current for specified heat dissipation (In) | | 250 A |
| Equipment heat dissipation, current-dependent | | 59.44 W |
| Ambient operating temperature - min | | -25 °C |
| Ambient operating temperature - max | | 70 °C |
| Ambient storage temperature - min | | -40 °C |
| Ambient storage temperature - max | | 70 °C |
| Design verification as per IEC/EN 61439 | | |
| 10.2.2 Corrosion resistance | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | Meets the product standard's requirements. |
| 10.2.5 Lifting | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |
| Additional information | | |
| Functions | | Disconnectors/main switches |

Technical data ETIM 9.0

| | | |
|---|----|--|
| Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EC000228) | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecl@ss13-27-37-04-09 [AJZ716018]) | | |
| Rated permanent current Iu | A | 250 |
| Rated voltage | V | 690 - 690 |
| Rated short-circuit breaking capacity Icu at 400 V, 50 Hz | kA | 150 |
| Overload release current setting | A | 0 - 0 |
| Adjustment range short-term delayed short-circuit release | A | 0 - 0 |
| Adjustment range undelayed short-circuit release | A | 2500 - 2500 |
| Power loss | W | 48 |
| Device construction | | Built-in device fixed built-in technique |
| Integrated earth fault protection | | No |
| Type of electrical connection of main circuit | | Screw connection |
| Suitable for DIN rail (top hat rail) mounting | | No |

| | | | |
|---|--|--|--------------|
| DIN rail (top hat rail) mounting optional | | | Yes |
| Number of auxiliary contacts as normally closed contact | | | 0 |
| Number of auxiliary contacts as normally open contact | | | 0 |
| Number of auxiliary contacts as change-over contact | | | 0 |
| With switched-off indicator | | | No |
| With integrated under voltage release | | | No |
| Number of poles | | | 3 |
| Position of connection for main current circuit | | | Front side |
| Type of control element | | | Rocker lever |
| Complete device with protection unit | | | Yes |
| Motor drive integrated | | | No |
| Motor drive optional | | | Yes |
| Degree of protection (IP) | | | IP20 |