

Terminal block, 1 pole, 250A, 11 output terminals, ALU



Part no. BPZ-KB-11/250-ALU
102705
EL Number 1243566
(Norway)

General specifications		
Product name		Eaton xEnergy Basic other accessory
Part no.		BPZ-KB-11/250-ALU
EAN		4015081025657
Product Length/Depth		49 millimetre
Product height		95.4 millimetre
Product width		44.5 millimetre
Product weight		0.455 kilogram
Compliances		RoHS conform
Certifications		IEC 60 947 -7 -1
Product Tradename		xEnergy Basic
Product Type		Accessories
Product Sub Type		Other
Delivery program		
Amperage rating		250 A
Number of poles		Single-pole
Technical Data - Electrical		
Voltage rating at AC Cu (IEC) - max		1000 V AC
Voltage rating at DC Cu (IEC) - max		1500 V DC
Rated peak withstand current		51 kA
Rated operation current (Ie) Cu (IEC)		200 A
Rated short-time withstand current (Icw)		21 kA
Technical Data - Mechanical		
Mounting method		Floor standing distribution board Surface mounting Flush mounting
Mounting position		Universal
Material		Aluminum
Degree of protection		IP10
Number of clamp positions per pole		12
Number of clamping units per pole		12
Terminal capacity (single/multi-wire)		2.5 mm ² -35 mm ² (outgoing) 2.5 mm ² - 16 mm ² (outgoing) 14 - 6 AWG (outgoing) 14 - 8 AWG (outgoing, fine wire (with sleeve)) 2 - 4/0 AWG (incoming) 2.5 mm ² - 10 mm ² (outgoing, fine wire (with sleeve)) 2 - 3/0 AWG (incoming, fine wire (with sleeve)) 14 - 6 AWG (outgoing, fine wire (with sleeve)) 14 - 8 AWG (outgoing) 14 - 2 AWG (outgoing) 14 - 4 AWG (outgoing, fine wire (with sleeve)) 2.5 mm ² - 16 mm ² (outgoing, fine wire (with sleeve)) 35 mm ² - 95 mm ² (incoming, fine wire (with sleeve)) 35 mm ² - 120 mm ² (incoming) 2.5 mm ² - 25 mm ² (outgoing, fine wire (with sleeve)) 2.5 mm ² - 10 mm ² (outgoing)
Conductor cross section (solid, solid-strand) - min		2.5 mm ²
Conductor cross section (solid, solid-strand) - max		120 mm ²
Clamp material		Brass Nickel plated
Torque rating		19 Nm - 21 Nm / 168.1 lbf - 185.8 lbf (incoming). 2 Nm - 7 Nm / 17.7 lbf - 62 lbf (outgoing)
Housing color		Light gray (RAL 7035)
Housing material		PA66

Design verification as per IEC/EN 61439 - technical data		
Heat deflection temperature		100 °C
Additional information		
Comparative tracking index (CTI)		600 V
Flame classification (UL 94)		V-0
Functions		Additional equipment
Special features		<p>Clicks on DIN-rail or on base plate. Save time on wiring. Save 80% on space used. Modular construction, 1-4 pole Systems can be built with several blocks. Material, hexagon socket set screw: Steel This power distribution block is suitable for ALU and CU conductors. Please pay attention to the common handling guidelines when connecting the aluminium conductors. Clean and brush the contact surfaces and lubricate them with an appropriate grease. As precaution the connections should get retightened regularly. Zinc plated (Hexagon socket set screw, Surface finish)</p>

Technical data ETIM 9.0

Energy distribution systems (EG000015) / Distributor assembly terminal blocks (EC001894)			
Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Distributor assembly terminal blocks (ecl@ss13-27-40-06-09 [AC0381016])			
Height		mm	95.4
Width		mm	44.5
Depth		mm	49
Max. rated current		A	250
Number of poles			1
Conductor cross section flexible (fine-strand) with cable end sleeve		mm ²	2.5 - 95
Conductor cross section solid (solid, stranded)		mm ²	2.5 - 120
Number of clamp positions per pole			12
With PE-rail			No
With N-rail			No