

Connection segment for 1-pole terminal block, L x W x H = 16 x 44 x 14 mm



Part no. BPZ-CB-44/14

102722

**EL Number
(Norway)**

2459298

General specifications		
Product name		Eaton xEnergy Basic other accessory
Part no.		BPZ-CB-44/14
EAN		4015081025824
Product Length/Depth		44 millimetre
Product height		16 millimetre
Product width		14 millimetre
Product weight		0.03 kilogram
Compliances		RoHS conform
Product Tradename		xEnergy Basic
Product Type		Accessories
Product Sub Type		Other
Delivery program		
Color		Other
Number of phases		1
Number of poles		Single-pole
Technical Data - Electrical		
Rated operational voltage (Ue) - max		690 V
Rated surge voltage		1 kV
Rated uninterrupted current (Iu)		125 A
Rated conditional short-circuit current (Iq)		0 kA
Rated short-time withstand current (Icw)		4.2 kA
Electric connection type		Fork
Technical Data - Mechanical		
Number of modular spacings		0
Cross section		20 mm ²
Pitch dimensions		0 mm
Suitable for number of devices		2
Additional information		
Features		Insulated
Suitable for		2 devices

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss13-27-37-13-06 [ACN992016])		
Number of phases		1
Number of poles		1
Suitable for number of devices		2
Module width	mm	0
Cross section	mm ²	20
Length	mm	44
Can be cut to size		No
Width in number of modular spacings		0
Rated permanent current Iu	A	125
Type of electric connection		Fork
Insulated		Yes

Rated surge voltage	kV	1
Conditioned rated short-circuit current I _q	kA	0
Max. rated operation voltage U _e	V	690
Rated short-time withstand current I _{cw}	kA	4.2
Suitable for devices with N-conductor		No
Suitable for devices with auxiliary switch		No
Colour		Other