



Bottom/Top coverstrip 75mm long, 35mm blind + 40mm foam gasket, IP20, for 425mm Sectionwidth, grey



Powering Business Worldwide™

Part no. **XLST2J4C**
 Catalog No. **107679**

EL-Nummer **2465264**
 (Norway)

Delivery program

Product range		Control centres XVTL
Basic function		Accessories
Product function		Accessories
Accessories		Bottom plates
Single unit/Complete unit		Accessories
Description		Bottom plates as blanking covers adjustable from 60 - 75 mm Cable bushings < # 50 mm possible when using 2 XSPBA... # 50 - 80 mm cable bushings possible when using an XSPBA... in conjunction with XVTL-BP/JL
Function		for downward separation and for cable entries
Material		Sheet steel 1.5 mm
Surface finish		RAL 7035, light grey
Information about equipment supplied		Including screws
Suitable for depth		60 - 75
Suitable for width		425
Cableway		< Ø 50 mm

Technical data ETIM 7.0

Cabinet enclosures (EG000011) / Component for installation (switchgear cabinet) (EC002620)		
Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Elements for switching cabinet, housing, rack / Component for installation (electrical cabinet) (ecl@ss10.0.1-27-18-28-11 [ACN627011])		
Model		Floor plate
Suitable for enclosure building width	mm	425
Suitable for enclosure building height	mm	0
Suitable for enclosure building depth	mm	0
Width	mm	325
Height	mm	20
Depth	mm	75
Max. load capacity	kg	0
Material		Metal
Colour		Grey
RAL-number		7035