

Wall enclosure with mounting plate, HxWxD=600x600x300mm

Part no. CS-66/300
111700
EL Number 2466124
(Norway)

General specifications	
Product name	Eaton xEffect CS enclosure single door
Part no.	CS-66/300
EAN	4015081112593
Product Length/Depth	300 millimetre
Product height	600 millimetre
Product width	600 millimetre
Product weight	25.17 kilogram
Compliances	UL CSA09 (may be provided with metal sub-panel, no back mounted components are allowed between sub-panel and the back sheet metal enclosure) RoHS conform UL 508A; CSA-C22.2 No.14; IEC/EN 62208; CE marking
Certifications	UL (Category Control Number NITW) IEC/EN 62208 UL (File No. E336299) In accordance with Directive 2015/863/EU of the European Parliament and Council UL CSA08 (request filed)
Product Tradename	xEffect CS
Product Type	Enclosure
Product Sub Type	Single door
Delivery program	
Type	Wall-mounting housing CS Wall-mounting housing with mounting plate
Color	Gray Light gray (RAL 7035)
Technical Data - Mechanical	
Design type	Canted and seam welded, including two M6 threaded bolts for earth conductor connections inside the enclosure.
Surface finishing	Powder coating Structured powder spray polyester based paint finish Semi-textured Gloss
Surface treatment	Structured powder spray polyester based paint finish
Mounting method	9 mm drilling dimensions for wall mounting (Back plate) Wall fastening Intermediate mounting
Mounting plate height	570 mm
Mounting plate material	Sheet steel, hot-galvanized
Mounting plate width	550 mm
Material	Steel Steel plate
Material thickness (body)	1.5 mm
Material thickness (bottom plate)	2 mm
Material thickness (door)	1.5 mm
Material quality	Other
Degree of protection	IK09 IK09 (impact resistance) 12 (NEMA) IP66 IP23 (with ventilating plates) IEC: IP66, indoor; UL/CSA Types 1, 12, indoor only.
Number of F3A flanges	2
Number of connector holes	0
Number of covers/doors	1
Number of hinges	2
Number of locks	2
Load capacity (door)	25 kg

Load capacity (mounting plate)		250 kg 500 kg payload, when brackets fitted in all four enclosure corners (vertically or horizontally) and the weights are symmetrically distributed within the enclosure.
Permissible load of the door(s) according to IEC 62208 - max		250 N
Permissible load of the enclosure according to IEC 62208 - max		2750 N
Permissible load of the mounting plate according to IEC 62208 - max		2500 N
Weight of mounted components - max		275 kg
Cover/door angle		120° door opening angle
Cover/door profile		2 door profiles
Cover/door type		Standard closure 3 mm double-ward key (door interlock) Door hinges on the right, can be converted by user Closed
Flange plate dimensions		172 mm x 432 mm
Installation site		Indoor installation
Installation type		Floor standing wall model
Thickness of mounting plate		2 mm
Climatic proofing		Damp heat, constant, to IEC 60068-2-78; Damp heat, cyclical, to IEC 60068-2-30
Temperature-rise verification as per IEC 60890		
Heat diss. ambient 35°C delta T: 20°C wall mount middle encl. top (IEC 60890)		57 W
Heat diss. ambient 35°C delta T: 35°C wall mount middle encl. top (IEC 60890)		115 W
Heat diss. ambient 35°C delta T: 20°C wall mount individ. encl. top (IEC 60890)		65 W
Heat diss. ambient 35°C delta T: 20°C wall mount starting encl. top (IEC 60890)		61 W
Heat diss. ambient 35°C delta T: 35°C wall mount individ. encl. top (IEC 60890)		131 W
Heat diss. ambient 35°C delta T: 35°C wall mount starting encl. top (IEC 60890)		123 W
Heat diss. wall mount individual encl. top		65 W
Heat diss. wall mount middle encl. top		57 W
Heat diss. wall mount starting encl. top		61 W
Thermal dissipation (Delta T = 20 K) according to IEC/TR 60890		65 W
Design verification as per IEC/EN 61439 - technical data		
Ambient operating temperature details		-25 °C - 40 °C
Design verification as per IEC/EN 61439		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply to enclosures without lifting aids.
10.2.6 Mechanical impact		IK09
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		IP66
10.4 Clearances and creepage distances		Is the panel builder's responsibility.
10.5 Protection against electric shock		< 0.1 Ω; meets the product standard's requirements.
10.6 Incorporation of switching devices and components		Is the panel builder's responsibility.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Ui = 1000 V AC
10.9.3 Impulse withstand voltage		Does not apply to basic enclosures as defined in EN 62208.
10.9.4 Testing of enclosures made of insulating material		Does not apply to metal enclosures.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility.
10.13 Mechanical function		Meets the product standard's requirements.
Additional information		
Features		Wall build in Pole fastening
Fitted with:		Mounting plate Including M6 threaded welded studs for earth conductor connections in the door:

		Cover Door
Functions		Floor standing enclosure
RAL-number		7035
Special features		Bottom plate enclosed, foamed gasket, can be unscrewed for F3A-... flanges or for assembly by user Foamed polyurethane sealing throughout. Impact resistance category IK09 to EN 62262. Sheet steel mounting plate Bottom plate with foamed gasket. Single door, door stop on the right, door opening angle 120° Door hinge pins with quick change technology. Standardized locking system with sash fastener. Powder coating RAL 7035 inside and outside Lock, 3 mm double ward key Including M6 threaded welded studs for earth conductor connections in the door Side plates without apertures Top plate without apertures
Suitable for		Metrical mounting
Used with		Industrial control panels

Technical data ETIM 9.0

Cabinet enclosures (EG000011) / Enclosure/cabinet (empty) (EC000261)			
Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Electrical cabinet (empty) / Electrical cabinet, Empty enclosures (ecl@ss13-27-18-01-01 [AGZ056021])			
Width		mm	600
Height		mm	600
Depth		mm	300
Material			Steel
Material quality			Other
Surface finishing			Powder coating
Colour			Grey
RAL-number			7035
Freestanding			No
Floor standing wall model			Yes
Suitable for wall mounting			Yes
Corner model			No
Intermediate mounting			Yes
Couplable			No
With mounting plate			Yes
Mounting plate depth-adjustable			No
Suitable for wall built-in			Yes
Pole fastening			Yes
With door			Yes
Number of doors			1
With glazed door			No
With ventilation door			No
With rear door			No
Number of locks			2
With cover			Yes
Transparent cover			No
Suitable for metrical mounting			Yes
Suitable for outdoor set-up			No
Pitched roof			No
Number of connector holes			0
Pre-stamping			No
EMC-version			No
Impact strength			IK09
Degree of protection (IP)			IP66
Degree of protection (NEMA)			12
Thermal dissipation (Delta T = 20 K) according to IEC/TR 60890		W	65
Max. permissible load of the enclosure according to IEC 62208		N	2750
Max. permissible load of the door(s) according to IEC 62208		N	250
Max. permissible load of the mounting plate according to IEC 62208		N	2500

