

Key-operated actuator, maintained, 2 positions, MS10, Key withdrawable:
0, I, Bezel: titanium

Part no. **M22-WRS-MS10**
111775

General specifications		
Product name		Eaton Moeller® series M22 Key-operated actuator
Part no.		M22-WRS-MS10
EAN		4015081113255
Product Length/Depth		70 millimetre
Product height		30 millimetre
Product width		30 millimetre
Product weight		0.034 kilogram
Compliances		CE Marked
Certifications		UL 508 IEC 60947-5 CSA Std. C22.2 No. 94-91 CSA Std. C22.2 No. 14-05 EN 60947-5 VDE CSA File No.: 012528 UL UL File No.: E29184 CE IEC/EN 60947 CSA-C22.2 No. 94-91 IEC/EN 60947-5 VDE 0660 CSA-C22.2 No. 14-05 CSA CSA Class No.: 3211-03 UL Category Control No.: NKCR DNV LR GL
Product Tradename		M22
Product Type		Key-operated actuator
Product Sub Type		None
Catalog Notes		Key withdraw convertible with coding adapters M22-XC-... Not suitable for master key systems
Features & Functions		
Bezel color		Titanium
Bezel material		Plastic
Design		Key operated Classical
Fitted with:		Front ring
Functions		Stay-put/spring-return function, can be changed with coding parts M22-XC-Y
Key code		MS10
General information		
Accessories		1 key included with supplied equipment.
Degree of protection		NEMA 4X, 13
Degree of protection (front side)		IP66
Lifespan, mechanical		100,000 Operations
Opening diameter		22.5 mm
Operating frequency		100 Operations/h
Operating torque		0.5 N·m
Product category		RMQ-Titan
Switching angle		60 °
Type		Key-operated button
Ambient conditions, mechanical		
Mounting position		As required
Shock resistance		30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

		Mechanical, According to IEC/EN 60068-2-27
Climatic environmental conditions		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Climatic proofing		Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Communication		
Connection to SmartWire-DT		With SWD-RMQ connections Yes
Actuator		
Actuator color		Black
Actuator function		Switching function latching Key withdrawable in position 0 Maintained Key withdrawable in position 1
Actuator type		Key
Number of switch positions		2
Contacts		
Force for positive opening - min		0 N
Design verification		
Equipment heat dissipation, current-dependent P _{vid}		0 W
Heat dissipation capacity P _{diss}		0 W
Heat dissipation per pole, current-dependent P _{vid}		0 W
Rated operational current for specified heat dissipation (I _n)		0 A
Static heat dissipation, non-current-dependent P _{vs}		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		Not applicable.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Front element for selector switch (EC000222)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for selector switches (ecl@ss13-27-37-12-13 [AKF031019])		
Number of switch positions		2
Type of control element		Key
Suitable for illumination		No
Colour control element		Black

Colour indicator light cap			Other
Construction type lens			Round
Hole diameter		mm	22.5
Width opening		mm	0
Height opening		mm	0
Switching function latching			Yes
Spring-return			No
With front ring			Yes
Material front ring			Plastic
Colour front ring			Titanium
Degree of protection (IP), front side			IP66
Degree of protection (NEMA)			4X, 13