



Connection cable, 4p, DC current, coupling m12 angled, open end, L=2m



Powering Business Worldwide™

Part no. CSDR4A4CY2202
Catalog No. 136279
Alternate Catalog No. CSDR4A4CY2202
EL-Nummer (Norway) 0004315395

Delivery program

Basic function			Accessories
Accessories			Connecting cables
Basic function			Accessories
Range			connecting cables
Length		mm	2000
Pin assignment			<p>1 = Brown 2 = White 3 = Blue 4 = Black</p>
Voltage type			DC
Number of poles			4 pole
Style output side			Cable end, open
Style input side			Coupling, angled
For use with			
For use with			DC sensors, 4 pole, 2, 3 or 4-wire connection, M12 RS2...-02... RS2...-11... RS4-02...

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

Technical data ETIM 7.0

Sensors (EG000026) / Sensor-actuator patch cord (EC001855)			
Electric engineering, automation, process control engineering / Cable, wire / Ready-made data cable / Assembled sensor actuator-line (ecl@ss10.0.1-27-06-03-11 [AFR601003])			
Number of poles			4
Type of electrical connection, field-sided			M12
Type of plug-in contact, field sided			Female (bus)
Positioning cable feed, field-sided			Angled
Type of electrical connection, box-sided			Other
Type of plug-in contact, box-sided			
Positioning cable feed, box-sided			Other
Cable length		m	2
Material of cable sheath			Other
Halogen free			No
Colour cable sheath			Other
With LED indication			No
Screened			No
Type of cable			Multi-core
Vulcanize			No
Material contact body			Other
Material of contact surface			Other
Permitted cable outer temperature after assembling without vibration		°C	40 - 70
Permitted cable outer temperature during assembling/handling		°C	40 - 70
Rated current In		A	0

Rated voltage	V	0
Continuity resistor	mOhm	0
Degree of protection (IP)		Other

Approvals

Product Standards		CE marking
-------------------	--	------------