



Connection cable, 4p, DC current, coupling m12 angled, open end, L=5m



Powering Business Worldwide™

Part no. CSDR4A4CY2205
Catalog No. 136282
Alternate Catalog No. CSDR4A4CY2205
EL-Nummer (Norway) 0004315396

Delivery program

| | | | |
|---------------------|--|----|--|
| Basic function | | | Accessories |
| Accessories | | | Connecting cables |
| Basic function | | | Accessories |
| Range | | | connecting cables |
| Length | | mm | 5000 |
| Pin assignment | | | <p>1 = Brown 2 = White 3 = Blue 4 = Black</p> |
| Voltage type | | | DC |
| Number of poles | | | 4 pole |
| Style output side | | | Cable end, open |
| Style input side | | | Coupling, angled |
| For use with | | | |
| For use with | | | DC sensors, 4 pole, 2, 3 or 4-wire connection, M12 RS2...-02... RS2...-11... RS4-02... |

Design verification as per IEC/EN 61439

| | | | |
|--|--|----|-----|
| Technical data for design verification | | | |
| Operating ambient temperature min. | | °C | -25 |
| Operating ambient temperature max. | | °C | 70 |

Technical data ETIM 7.0

| | | | |
|---|--|----|--------------|
| Sensors (EG000026) / Sensor-actuator patch cord (EC001855) | | | |
| Electric engineering, automation, process control engineering / Cable, wire / Ready-made data cable / Assembled sensor actuator-line (ecl@ss10.0.1-27-06-03-11 [AFR601003]) | | | |
| Number of poles | | | 4 |
| Type of electrical connection, field-sided | | | M12 |
| Type of plug-in contact, field sided | | | Female (bus) |
| Positioning cable feed, field-sided | | | Angled |
| Type of electrical connection, box-sided | | | Other |
| Type of plug-in contact, box-sided | | | |
| Positioning cable feed, box-sided | | | Other |
| Cable length | | m | 5 |
| Material of cable sheath | | | Other |
| Halogen free | | | No |
| Colour cable sheath | | | Other |
| With LED indication | | | No |
| Screened | | | No |
| Type of cable | | | Multi-core |
| Vulcanize | | | No |
| Material contact body | | | Other |
| Material of contact surface | | | Other |
| Permitted cable outer temperature after assembling without vibration | | °C | 40 - 70 |
| Permitted cable outer temperature during assembling/handling | | °C | 40 - 70 |
| Rated current In | | A | 0 |

| | | |
|---------------------------|------|-------|
| Rated voltage | V | 0 |
| Continuity resistor | mOhm | 0 |
| Degree of protection (IP) | | Other |

Approvals

| | | |
|-------------------|--|------------|
| Product Standards | | CE marking |
|-------------------|--|------------|