

## Connection cable, 4p, DC current, coupling M12 flat, open end, L=5m

**Part no.** CSDS4A4CY2205  
**136294**  
**EL Number** 4315401  
**(Norway)**

General specifications		
Product name		Eaton Moeller® series CSDS Accessory Connection cable
Part no.		CSDS4A4CY2205
EAN		4015081330829
Product Length/Depth		203.2 millimetre
Product height		38.1 millimetre
Product width		177.8 millimetre
Product weight		0.172 kilogram
Certifications		CE
Product Tradename		CSDS
Product Type		Accessory
Product Sub Type		Connection cable
Product Specification Details		
Ambient operating temperature - max		70 °C
Ambient operating temperature - min		-25 °C
Cable length		5 m
Cable sheath material		Other
Cable type		Multi-core Cable end, open, Output side Coupling, straight, Input side
Color cable sheath		Yellow
Contact body material		Other
Contact surface material		Other
Continuity resistor		0 mΩ
Degree of protection		Other
EL number		4315401
Electrical connection type (box-sided)		Other
Electrical connection type (field-sided)		M12
Nominal current		0 A
Number Of Poles		Four-pole
Permitted temperature of outer cable (assembled) without vibration - max		70 °C
Permitted temperature of outer cable (assembled) without vibration - min		40 °C
Permitted temperature of outer cable (assembling/handling) - max		70 °C
Permitted temperature of outer cable (assembling/handling) - min		40 °C
Plug-in contact type (box-sided)		Male (plug)
Plug-in contact type (field-sided)		Female (bus)
Positioning cable feed (box-sided)		Other
Positioning cable feed (field-sided)		Straight
Product category		Accessories
Rated operational voltage (Ue) - max		0 V
Type		Connecting cables
Voltage type		DC

### Technical data ETIM 9.0

Sensors (EG000026) / Sensor-actuator patch cord (EC001855)		
Electric engineering, automation, process control engineering / Cable, wire / Ready-made data cable / Assembled sensor/actuator adapter, with cable (ecl@ss13-27-06-03-13 [AFR625008])		
Number of poles		4
Type of electrical connection, field-sided		M12

Type of plug-in contact, field sided			Female (bus)
Positioning cable feed, field-sided			Straight
Type of electrical connection, box-sided			Other
Type of plug-in contact, box-sided			Male (plug)
Positioning cable feed, box-sided			Other
Cable length		m	5
Material of cable sheath			Other
Halogen free			No
Colour cable sheath			Yellow
With LED indication			No
Screened			No
Cable type			Multi-core
Vulcanize			No
Material contact body			Other
Material of contact surface			Other
Permitted cable outer temperature after assembling without vibration		°C	40 - 70
Permitted cable outer temperature during assembling/handling		°C	40 - 70
Rated current I <sub>n</sub>		A	0
Rated voltage		V	0
Continuity resistance		mOhm	0
Degree of protection (IP)			Other