



Plug, M12, 4p, flat

Part no. CSDSM4
 Catalog No. 136297
 Alternate Catalog No. CSDSM4

Delivery program

Basic function			Accessories
Accessories			Plug
Connection type			Screwed terminal
Number of poles			4 pole
Design (outer dimensions)		mm	straight
For use with			
For use with			DC sensors, 4 pole, 2, 3 or 4-wire connection, M12
Degree of Protection			IP67
Ambient temperature			
Operation	9	°C	-40 - +85
Terminal capacity			
Flexible		AWG	24 - 18
flexible		mm ²	0.25 - 0.75

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-40
Operating ambient temperature max.		°C	85

Technical data ETIM 6.0

Sensors (EG000026) / Sensor-actuator connector (EC002062)			
Electric engineering, automation, process control engineering / Connector system / Industry connector / Sensor-actuator connector (sensor technology acc.) (ecl@ss8.1-27-44-01-04 [ACN876008])			
Type of connection socket for actuators and sensors			M12
Model			Male (plug)
Position cable feed			Straight
Number of poles			4
Type of electric connection			Screw connection
Screened			Yes
Core cross section		mm ²	0
Permitted cable diameter		mm	0 - 0
Material housing			Other

Approvals

Product Standards			CE marking
-------------------	--	--	------------