



Surge arrester complete, 3-pole, 280VAC, 3x10kA

**Part no.** SPET2-280/3  
**Catalog No.** 168692  
**Alternate Catalog No.** SPET2-280/3

## Delivery program

Products		Surge arresters
Application field		Residential buildings Utility buildings Open areas

## Technical data ETIM 7.0

Earthing, lightning and surge protection (EG000021) / Surge protection device for power supply systems (EC000941)		
Electric engineering, automation, process control engineering / Protection installation, device (electric) / Surge protection device (inner lightning protection) / Surge protection device for power supply systems (ecl@ss10.0.1-27-13-08-05 [ACN278011])		
System configuration DC		No
System configuration IT		No
System configuration TN		No
System configuration TN-C		No
System configuration TN-C-S		No
System configuration TN-S		No
System configuration TT		No
System configuration other		Yes
Number of conductors (without earthing)		3
Nominal discharge surge current (8/20)	kA	10
Nominal voltage AC	V	280
Nominal voltage DC	V	0
Short-circuit breaking capacity (Iscbr)	kA	0
Max. continuous voltage AC	V	280
Max. discharge surge current (8/20)	kA	20
Max. continuous voltage DC	V	0
Mounting method		DIN rail (top hat rail) 35 mm
Construction size		3 modular spacing
Max. PV-voltage	V	0
Voltage protection level	kV	1.2
Max. conductor cross section solid (solid, stranded)	mm <sup>2</sup>	25
Max. conductor cross section flexible (fine-strand)	mm <sup>2</sup>	0
Voltage protection level L-N	kV	0
Voltage protection level N-PE	kV	0
With remote signalling contact		No
Integrated backup fuse		No
Signalling at the device		Optic
Category type 2		Yes
Degree of protection (IP)		IP20