

Cable for variable frequency drives (1 m, RJ45/RJ45)



Part no. DX-CBL-RJ45-1M0
169138
EL Number 4137455
(Norway)

General specifications		
Product name		Eaton DX Connection cable
Part no.		DX-CBL-RJ45-1M0
EAN		4015081656172
Product Length/Depth		38 millimetre
Product height		170 millimetre
Product width		120 millimetre
Product weight		0.1 kilogram
Certifications		UL Certified by UL for use in Canada UL report applies to both US and Canada CE IEC/EN61800-3 CSA-C22.2 No. 14 UL 508C UL File No.: E172143 UL Category Control No.: NMMS, NMMS7 IEC/EN61800-5
Product Tradename		DX
Product Type		Accessory
Product Sub Type		Connection cable
General information		
Accessory/spare part type		Cable
Degree of protection		IP00
Product Category		Accessories
Suitable for		Branch circuits, (UL/CSA)
Type		Patch cord with RJ45 plugs, 8 pole
Used with		DB1
Climatic environmental conditions		
Ambient operating temperature - max		50 °C
Ambient operating temperature - min		-10 °C
Design verification		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Accessories/spare parts for frequency controller (EC002025)			
Electric engineering, automation, process control engineering / Electrical drive / Static frequency converter / Static frequency converter (accessories) (ecl@ss13-27-02-31-92 [AFR303008])			
Type of accessory/spare part			Cable
Accessory			Yes
Spare part			No