

Continuous light module; yellow;high power LED;24 V

Part no. SL7-L24-Y-HP
171431
EL Number 4137686
(Norway)

General specifications		
Product name		Eaton Moeller® series SL7 Continuous light module
Part no.		SL7-L24-Y-HP
EAN		4015081677634
Product Length/Depth		73 millimetre
Product height		73 millimetre
Product width		73 millimetre
Product weight		0.088 kilogram
Certifications		UL Category Control No.: NKCR CSA Class No.: NKCR7 Certified by UL for use in Canada IEC/EN 60947-5-1 UL File No.: E29184 CSA-C22.2 No. 14-10 UL IEC/EN 60529 UL report applies to both US and Canada UL 508 CSA-C22.2 No. 94-91 CE
Product Tradename		SL7
Product Type		Continuous light module
Product Sub Type		None
Features & Functions		
Color		Yellow
Enclosure color		Black
Functions		Continuous light
Light modules		High Performance LED
Number of modules		Max. 10 (with base for mounting on both sides) Max. 5 (with standard base)
General information		
Connection to SmartWire-DT		No
Current consumption		0.17 - 0.2 A, at 24 V AC/DC
Degree of protection		IP66 NEMA 4X
Lifespan, electrical		50,000 h
Light type		Continuous light
Material		Cap: Polycarbonate (PC) Enclosure: Polycarbonate (PC)
Mounting position		As required
Overvoltage category		III
Pollution degree		3
Product Category		SL signal towers
Radiation angle		360 °
Rated impulse withstand voltage (Uimp)		4000 V AC
Shock resistance		Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Type		Continuous light module High-performance LED for maximum signaling effect
Voltage type		AC/DC
Climatic environmental conditions		
Ambient operating temperature - min		-30 °C
Ambient operating temperature - max		60 °C
Climatic proofing		Damp heat, constant, to IEC 60068-2-78

		Damp heat, cyclic, to IEC 60068-2-30
Electrical rating		
Leakage current		0.003 A
Rated insulation voltage (Ui)		250 V
Rated operational voltage (Ue) at AC - min		18 V
Rated operational voltage (Ue) at AC - max		26 V
Rated operational voltage (Ue) at DC - min		18 V
Rated operational voltage (Ue) at DC - max		30 V

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Optical module for signal tower (EC000232)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Optical module for signal tower (ecl@ss13-27-37-12-20 [AKF038019])		
Function		Continuous light
Repetition frequency settable		No
Colour		Yellow
Outer diameter	mm	73
Operating voltage AC 50 Hz	V	18 - 26
Operating voltage AC 60 Hz	V	18 - 26
Operating voltage DC	V	18 - 30
Voltage type		AC/DC
Power consumption	W	
Lamp type		LED
Housing colour		Black
Degree of protection (IP)		IP66
Degree of protection (NEMA)		4X