

Handle, red/yellow, lockable, for metal shaft, for padlock, for P1

 Part no. **SVB-P1/M**
172840

General specifications		
Product name		Eaton Moeller® series SVB Accessory Handle
Part no.		SVB-P1/M
EAN		4015081694228
Product Length/Depth		80 millimetre
Product height		65 millimetre
Product width		65 millimetre
Product weight		0.09 kilogram
Compliances		NOM-NYCE Marked
Certifications		UL Listed
Product Tradename		SVB
Product Type		Accessory
Product Sub Type		Handle
Features & Functions		
Color		Red
Features		Lockable
Fitted with:		Padlocking feature
Functions		Emergency stop function Emergency switching off function
Locking facility		Lockable with a maximum of 3 padlocks
Locking mechanism		Lockable in the 0 (Off) position (interlock)
General information		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		50 °C
Degree of protection		NEMA Other
Suitable for		Emergency stop Only for main switch Switch disconnecter
Switching angle		90 °
Type		Assembly kit Main switch assembly kit With red rotary handle and yellow locking ring
Design verification		
Equipment heat dissipation, current-dependent P _{vid}		0 W
Heat dissipation capacity P _{diss}		0 W
Heat dissipation per pole, current-dependent P _{vid}		0 W
Rated operational current for specified heat dissipation (I _n)		0 A
Static heat dissipation, non-current-dependent P _{vs}		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			Not applicable.
10.11 Short-circuit rating			Not applicable.
10.12 Electromagnetic compatibility			Not applicable.
10.13 Mechanical function			Not applicable.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Handle for power circuit breaker (EC000229)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Handle for switch devices (ecl@ss13-27-37-04-14 [AKF012019])			
With restart blockage			No
With key lock			No
Padlock locking			No
Colour			Red
Suitable for emergency stop			Yes
With extension shaft			No
Suitable for power circuit breaker			No
Suitable for switch disconnecter			Yes
Degree of protection (NEMA)			Other