

IKA standard distribution board, IP65 without clamps

Part no. IKA-1/8-OT
174205
EL Number 1702939
(Norway)

| General specifications | | |
|--|--|--|
| Product name | | Eaton xComfort IKA standard series |
| Part no. | | IKA-1/8-OT |
| EAN | | 4015081706679 |
| Product Length/Depth | | 115 millimetre |
| Product height | | 231 millimetre |
| Product width | | 238 millimetre |
| Product weight | | 0.84 kilogram |
| Compliances | | RoHS conform |
| Certifications | | EN 62208 IEC/EN 60670-24 |
| Product Tradename | | xComfort IKA |
| Product Type | | Standard series |
| Product Sub Type | | None |
| Delivery program | | |
| Type | | Basic device IKA standard distribution board Installation distribution board |
| Application | | Indoor (installation site) |
| Color | | Gray Light gray (RAL 7035) |
| Technical Data - Electrical | | |
| Voltage rating at AC | | 415 V AC |
| Frequency rating of contacts | | 50 Hz |
| Technical Data - Mechanical | | |
| Closure type | | Other |
| Enclosure material | | Plastic |
| Width in number of modular spacings | | 8 |
| Mounting method | | DIN-rail Surface mounting Surface mounted (plaster) |
| Material | | ABS (plastic) |
| Degree of protection | | IP65 IK08 (impact resistance) |
| Number of module space units per row | | 8 |
| Number of rows | | 1 |
| Terminal type | | Without terminals |
| Built-in depth | | 70 mm |
| Built-in height | | 0 mm |
| Built-in width | | 0 mm |
| Internal depth | | 60 mm |
| Cover/door color | | Transparent |
| Cover/door model | | With notch |
| Cover/door type | | Door Single |
| Module rack type | | Single-rail |
| Protective shrouding material | | Plastic |
| Temperature-rise verification as per IEC 60890 | | |
| Heat diss. ambient 35°C delta T:20°C wall mount individ. encl. top (IEC 60890) | | 14 W |
| Heat diss. ambient 35°C delta T:35°C wall mount individ. encl. top (IEC 60890) | | 29 W |
| Design verification as per IEC/EN 61439 - technical data | | |

| | | | |
|--|--|--|--|
| Ambient operating temperature details | | | -25 °C - 40 °C |
| Design verification as per IEC/EN 61439 | | | |
| 10.2.2 Corrosion resistance | | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | | | 650 °C; meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | | Not relevant to indoor installations. |
| 10.2.5 Lifting | | | Does not apply to enclosures without lifting aids. |
| 10.2.6 Mechanical impact | | | IK08 |
| 10.2.7 Inscriptions | | | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | | | IP65 |
| 10.4 Clearances and creepage distances | | | Is the panel builder's responsibility. |
| 10.5 Protection against electric shock | | | Protection class 2, therefore not applicable. |
| 10.6 Incorporation of switching devices and components | | | Is the panel builder's responsibility. |
| 10.7 Internal electrical circuits and connections | | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | | U _i = 1000 V AC |
| 10.9.3 Impulse withstand voltage | | | 3.3 kV |
| 10.9.4 Testing of enclosures made of insulating material | | | Meets the product standard's requirements. |
| 10.10 Temperature rise | | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | | Is the panel builder's responsibility. |
| 10.12 Electromagnetic compatibility | | | Is the panel builder's responsibility. |
| 10.13 Mechanical function | | | Meets the product standard's requirements. |
| Additional information | | | |
| Fitted with: | | | Locking screws can be sealed Basic device Sealing caps Device support rails Current circuit designation |
| Functions | | | Extension possible Basic device |
| Protection class | | | II (totally insulated) |
| RAL-number | | | 7035 |
| Special features | | | IP65 Protection Class II Plastic enclosure gray (RAL 7035) |
| Used with | | | Installation distribution board Basic device IKA standard distribution board |

Technical data ETIM 9.0

| | | | |
|---|--|----|-----------------|
| Distribution boards (EG000023) / Small distribution board (EC000214) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Electrical distribution system (including small distribution board) / Small distribution board (ecI@ss13-27-14-24-09 [ACN387016]) | | | |
| Mounting method | | | Surface mounted |
| Number of rows | | | 1 |
| Width in number of modular spacings | | | 8 |
| Type of covering | | | Door |
| Cover model | | | With notch |
| Type of door | | | Single |
| Transparent cover/door | | | Yes |
| Signal passing door | | | No |
| With lock | | | No |
| Type of closure | | | Other |
| Housing material | | | Plastic |
| Built-in depth | | mm | 70 |
| Built-in height | | mm | 0 |
| Built-in width | | mm | 0 |
| Inner depth | | mm | 60 |
| Earthing terminal block | | | No |

| | | | |
|---------------------------|--|----|------|
| Neutral terminal block | | | No |
| DIN-rail | | | Yes |
| With mounting plate | | | No |
| Extension possible | | | Yes |
| EMC-version | | | No |
| UV resistant | | | No |
| Colour | | | Grey |
| RAL-number | | | 7035 |
| Degree of protection (IP) | | | IP65 |
| Height | | mm | 231 |
| Width | | mm | 238 |
| Depth | | mm | 115 |