





Main switch, T8, 315 A, surface mounting, 3 contact unit(s), 6 pole, 1 N/O, 1 N/C, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) position

Part no. T8-3-8342/I48/SVB-SW/HI11  
Catalog No. 201449

Delivery program

Product range			Main switch maintenance switch Repair switch												
Part group reference			T8												
Stop Function			STOP function  With black rotary handle and locking ring												
Information about equipment supplied			with KS4-CI and K150/1/BR: Ingress protection IP64												
Number of poles			6 pole												
Auxiliary contacts															
		N/O	1												
		N/C	1												
Locking facility			Lockable in the 0 (Off) position												
Degree of Protection			IP65												
			<div>totally insulated</div>												
Design			surface mounting  												
Contact sequence			<div><table><tr><td>1</td><td>2</td><td>3</td><td>4</td><td>5</td><td>6</td></tr><tr><td>110</td><td>112</td><td>113</td><td>212</td><td>213</td><td>102</td></tr></table></div>	1	2	3	4	5	6	110	112	113	212	213	102
1	2	3	4	5	6										
110	112	113	212	213	102										
Switching angle		°	90												
Design number			8342												
Function															
Motor rating AC-23A, 50 - 60 Hz															
400 V	P	kW	132												
Rated uninterrupted current	I <sub>u</sub>	A	315												
Note on rated uninterrupted current I <sub>u</sub>			Rated uninterrupted current I <sub>u</sub> is specified for max. cross-section. Open = 315, enclosed= 275 A												
Number of contact units		contact unit(s)	3												

## Technical data

### General

Standards			IEC/EN 60947, VDE 0660, IEC/EN 60204 Switch-disconnector according to IEC/EN 60947-3
Climatic proofing			Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Ambient temperature			
Enclosed		°C	-25 - +40
Overvoltage category/pollution degree			III/3
Rated impulse withstand voltage	U <sub>imp</sub>	V AC	8000
Mounting position			As required

### Contacts

Mechanical variables			
Number of poles			6 pole
Auxiliary contacts			
		N/O	1
		N/C	1
Electrical characteristics			
Rated operational voltage	U <sub>e</sub>	V AC	690
Rated uninterrupted current	I <sub>u</sub>	A	315
Note on rated uninterrupted current I <sub>u</sub>			Rated uninterrupted current I <sub>u</sub> is specified for max. cross-section. Open = 315, enclosed= 275 A
Load rating with intermittent operation, class 12			
AB 25 % DF		x I <sub>e</sub>	2
AB 40 % DF		x I <sub>e</sub>	1.6
AB 60 % DF		x I <sub>e</sub>	1.3
Short-circuit rating			
Fuse		A gG/gL	315
Rated short-time withstand current (1 s current)	I <sub>cw</sub>	A <sub>rms</sub>	4200
Note on rated short-time withstand current I <sub>cw</sub>			Current for a time of 1 second
Rated conditional short-circuit current	I <sub>q</sub>	kA	5

### Switching capacity

cos φ rated making capacity as per IEC 60947-3		A	2390
Rated breaking capacity cos φ to IEC 60947-3		A	
230 V		A	1910
400/415 V		A	1800
500 V		A	1200
690 V		A	420
Safe isolation to EN 61140			
between the contacts		V AC	440
Current heat loss per contact at I <sub>e</sub>		W	11
Current heat loss per auxiliary circuit at I <sub>e</sub> (AC-15/230 V)		CO	0.2
Lifespan, mechanical	Operations	x 10 <sup>6</sup>	> 0.1
Maximum operating frequency	Operations/h		50
AC			
AC-3			
Rating, motor load switch	P	kW	
220 V 230 V	P	kW	37
230 V Star-delta	P	kW	37
400 V 415 V	P	kW	55
400 V Star-delta	P	kW	55
500 V	P	kW	37
500 V Star-delta	P	kW	37
690 V	P	kW	37
690 V Star-delta	P	kW	37
Rated operational current motor load switch			

230 V	I <sub>e</sub>	A	126
400V 415 V	I <sub>e</sub>	A	105
400 V star-delta	I <sub>e</sub>	A	105
500 V	I <sub>e</sub>	A	78
500 V star-delta	I <sub>e</sub>	A	78
690 V	I <sub>e</sub>	A	42
AC-21A			
Rated operational current switch			
440 V	I <sub>e</sub>	A	315
AC-23A			
Motor rating AC-23A, 50 - 60 Hz			
230 V	P	kW	
230 V	P	kW	75
400 V 415 V	P	kW	132
500 V	P	kW	132
690 V	P	kW	37
Rated operational current motor load switch			
230 V	I <sub>e</sub>	A	239
400 V 415 V	I <sub>e</sub>	A	245
500 V	I <sub>e</sub>	A	184
690 V	I <sub>e</sub>	A	42
DC			
DC-1, Load-break switches L/R = 1 ms			
Rated operational current			
	I <sub>e</sub>	A	315
Voltage per contact pair in series			
		V	42
DC-23A, motor load switch L/R = 15 ms			
24 V			
Rated operational current			
	I <sub>e</sub>	A	250
Contacts			
		Quantity	1
48 V			
Rated operational current			
	I <sub>e</sub>	A	250
Contacts			
		Quantity	2
60 V			
Rated operational current			
	I <sub>e</sub>	A	125
Contacts			
		Quantity	3
120 V			
Rated operational current			
	I <sub>e</sub>	A	50
Contacts			
		Quantity	3
DC-13, Control switches L/R = 50 ms			
Rated operational current			
	I <sub>e</sub>	A	250
Control circuit reliability at 24 V DC, 10 mA	Fault probability	H <sub>F</sub>	< 10 <sup>-5</sup> , < 1 failure in 100,000 switching operations

### Terminal capacities

Solid or stranded		mm <sup>2</sup>	185
Flat conductor connection with busbars		mm <sup>2</sup>	1 x (25 x 5) 2 x (20 x 3)
Terminal screw			M12
Tightening torque for terminal screw		Nm	14

### Technical safety parameters:

Notes			B10 <sub>d</sub> values as per EN ISO 13849-1, table C1
-------	--	--	---

### Rating data for approved types

Terminal capacity			
Terminal screw			M12
Tightening torque		lb-in	125

## Design verification as per IEC/EN 61439


Technical data for design verification			
Rated operational current for specified heat dissipation	I <sub>n</sub>	A	315
Heat dissipation per pole, current-dependent	P <sub>vid</sub>	W	11
Equipment heat dissipation, current-dependent	P <sub>vid</sub>	W	0
Static heat dissipation, non-current-dependent	P <sub>vs</sub>	W	0
Heat dissipation capacity	P <sub>diss</sub>	W	0
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	40
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			UV resistance only in connection with protective shield.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9 Insulation properties			
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 7.0


Low-voltage industrial components (EG000017) / Switch disconnecter (EC000216)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Switch disconnecter (ec1@ss10.0.1-27-37-14-03 [AKF060013])			
Version as main switch			Yes
Version as maintenance-/service switch			Yes
Version as safety switch			No
Version as emergency stop installation			No
Version as reversing switch			No
Number of switches			1
Max. rated operation voltage U <sub>e</sub> AC		V	690
Rated operating voltage		V	690 - 690
Rated permanent current I <sub>u</sub>		A	315
Rated permanent current at AC-23, 400 V		A	245
Rated permanent current at AC-21, 400 V		A	315
Rated operation power at AC-3, 400 V		kW	55
Rated short-time withstand current I <sub>cw</sub>		kA	4.2
Rated operation power at AC-23, 400 V		kW	132

Switching power at 400 V	kW	132
Conditioned rated short-circuit current I <sub>q</sub>	kA	5
Number of poles		6
Number of auxiliary contacts as normally closed contact		1
Number of auxiliary contacts as normally open contact		1
Number of auxiliary contacts as change-over contact		0
Motor drive optional		No
Motor drive integrated		No
Voltage release optional		No
Device construction		Complete device in housing
Suitable for ground mounting		Yes
Suitable for front mounting 4-hole		No
Suitable for front mounting centre		No
Suitable for distribution board installation		No
Suitable for intermediate mounting		No
Colour control element		Black
Type of control element		Door coupling rotary drive
Interlockable		Yes
Type of electrical connection of main circuit		Other
Degree of protection (IP), front side		IP65
Degree of protection (NEMA)		Other

Dimensions



The CI48 enclosure has a top cover height of 275 mm!



$$d = 4 - 8 \text{ mm}$$

$$b + d \leq 47 \text{ mm}$$

$$d = 0.16 - 0.31''$$

$$b + d \leq 1.85''$$

≤ 3 padlocks

### Additional product information (links)

#### IL03801017Z (AWA1150-1606) Rotary switch: Main switch

IL03801017Z (AWA1150-1606) Rotary switch: Main switch	<a href="ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL03801017Z2018_04.pdf">ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL03801017Z2018_04.pdf</a>
Display flip catalog page.	<a href="http://ecat.moeller.net/flip-cat/?edition=K115A&amp;startpage=130">http://ecat.moeller.net/flip-cat/?edition=K115A&amp;startpage=130</a>
Technical overview cam switch, switch-disconnector	<a href="http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.2">http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.2</a>
System overview cam switch T	<a href="http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.4">http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.4</a>
System overview switch-disconnector P	<a href="http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.6">http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.6</a>
Key to part numbers Cam switch	<a href="http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.8">http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.8</a>
Key to part numbers Switch-disconnector	<a href="http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.8">http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.8</a>
Switches for ATEX	<a href="http://www.coopercrouse-hinds.eu/en/products/25-ex-safety-and-main-current-switches.html">http://www.coopercrouse-hinds.eu/en/products/25-ex-safety-and-main-current-switches.html</a>