




Flashing light, 230VAC, white

Part no. SL-BL230-W
Catalog No. 205327
Alternate Catalog No. SL-BL230-W

Delivery program

| | | | |
|----------------------------|----------------|---|--|
| Product range | | | SL signal towers |
| Degree of Protection | | | IP54 |
| Single unit/Complete unit | | | Element |
| Description | | | without light elements Frequency f ~ 1 Hz |
| Rated operational voltage | U _e | V | 230 V AC |
| Colour | | | white |
| | | |  |
| Connection to SmartWire-DT | | | no |

Design verification as per IEC/EN 61439

| | | | |
|--|--|----|-----|
| Technical data for design verification | | | |
| Operating ambient temperature min. | | °C | -25 |
| Operating ambient temperature max. | | °C | 55 |

Technical data ETIM 5.0

| | | | |
|--|--|----|---------------|
| Low-voltage industrial components (EG000017) / Optical module for signal tower (EC000232) | | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Optical module for signal tower (ecl@ss8-27-37-12-20 [AKF038010]) | | | |
| Function | | | Blinker light |
| Colour | | | Clear |
| Outer diameter | | mm | 58 |
| Degree of protection (IP) | | | IP54 |
| Operating voltage at AC 50 Hz | | V | 230 - 230 |
| Operating voltage at AC 60 Hz | | V | 230 - 230 |
| Operating voltage at DC | | V | 0 - 0 |
| Voltage type | | | AC |
| Type of lamp | | | None |
| Colour housing | | | - |

Approvals

| | | | |
|-----------------------------|--|--|--|
| Product Standards | | | IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94-91; CE marking |
| UL File No. | | | E29184 |
| UL Category Control No. | | | NKCR |
| CSA File No. | | | 012528 |
| CSA Class No. | | | 3211-03 |
| North America Certification | | | UL listed, CSA certified |

Dimensions



Additional product information (links)

IL04716024Z (AWA1160-1685) Pillar lamps

IL04716024Z (AWA1160-1685) Pillar lamps

https://es-assets.eaton.com/DOCUMENTATION/AWA_INSTRUCTIONS/IL04716024Z2018_05.pdf