



Filament lamp, 24 V, BA15d, 5-7W

Part no. SL-L24
Catalog No. 205348
Alternate Catalog No. SL-L24

Delivery program

Product range			SL signal towers
Single unit/Complete unit			Stand-alone device
			Socket size BA-15d Power 5 - 7 W
Lifespan to EN 60064 at $t_a = +25\text{ }^\circ\text{C}$	t_{mean} (AC)	h	2000
Rated operational voltage	U_e	V	24 V
Connection to SmartWire-DT			no

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		$^\circ\text{C}$	-25
Operating ambient temperature max.		$^\circ\text{C}$	55

Technical data ETIM 7.0

Lamps (EG000028) / Indication- and signalling lamp (EC000399)			
Electric engineering, automation, process control engineering / Lighting installation, device / Light medium / Indication- and signal lamp (ecl@ss10.0.1-27-11-06-31 [AKE242014])			
Lamp power		W	5 - 7
Lamp voltage		V	24 - 24
Luminous flux		lm	0
Socket			BA15d
Technology			Incandescent lamp
Lamp shape			Pear-shape
Halogen			No
Krypton			No
Xenon			No
Colour			None
Colour temperature		K	2800
Diameter		mm	0
Total length		mm	0
Suitable for torches			No
Suitable for pointer			Yes
Suitable for round flashing luminaire			
Nominal current		mA	250
Average nominal lifespan		h	3000
Energy efficiency class			

Approvals

Product Standards			IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94-91; CE marking
UL File No.			E29184
UL Category Control No.			NKCR
CSA File No.			012528
CSA Class No.			3211-03
North America Certification			UL listed, CSA certified

Additional product information (links)

IL04716024Z (AWA1160-1685) Pillar lamps

