

Star-point bridge, For use with DILM185A - DILM400



Part no. DILM400-XS1
208291
EL Number 4134017
(Norway)

General specifications	
Product name	Eaton Moeller® series DILM star-point bridge
Part no.	DILM400-XS1
EAN	4015082082918
Product Length/Depth	6 millimetre
Product height	30 millimetre
Product width	120 millimetre
Product weight	0.31 kilogram
Certifications	CSA Class No.: 3211-04 CSA File No.: 012528 CSA-C22.2 No. 14-05 CSA IEC/EN 60947-4-1 UL 508 UL File No.: E36332 UL UL Category Control No.: NLRV CE
Product Tradename	DILM
Product Type	Accessory
Product Sub Type	Star-point bridge
General information	
Accessory/spare part type	Connecting bridge
Fitted with:	Cover for protection against accidental contact
Product category	Accessories
Climatic environmental conditions	
Ambient operating temperature - min	-40 °C
Ambient operating temperature - max	60 °C
Design verification	
Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdiss	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	0 A
Static heat dissipation, non-current-dependent Pvs	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.

10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Accessories/spare parts for low-voltage switch technology (EC002498)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Component for low-voltage switching technology (accessories) (ecl@ss13-27-37-13-92 [AKN570018])			
Type of accessory/spare part			Connecting bridge
Accessory			Yes
Spare part			No