

**Part no.**                      **CI-K2-80-K**  
**211108**

<b>General specifications</b>		
Product name		Eaton Moeller® series CI-K Insulated enclosure
Part no.		CI-K2-80-K
EAN		4015082111083
Product Length/Depth		181 millimetre
Product height		100 millimetre
Product width		100 millimetre
Product weight		0.342 kilogram
Certifications		IEC/EN 60529 UL94: HB DIN EN 62208 UL94: VO/1.5 mm thickness IEC 60068-2-11
Product Tradename		CI-K
Product Type		Insulated enclosure
Product Sub Type		None
Catalog Notes		Lamp indicator L... can be mounted in base knock-out M20/M25 Membrane grommets, cable glands Chapter 14, Accessories Transparent hinged cover for devices requiring 2 to 4 space units
<b>Features &amp; Functions</b>		
Enclosure color		Light gray, Cover (RAL 7035) Black (RAL 9005) Light gray, Operator (RAL 7035)
Enclosure material		1.0 x 10 <sup>13</sup> (Surface resistance to IEC 60093) Plastic
Features		UV resistance beneath protective shield Halogen free
Fitted with:		Hinged cover Control cable entry
Knockouts		Metric cable entry knockouts at the top, bottom and back plate Hard metric cable entry knockouts
<b>General information</b>		
Cover material		Glass-fiber reinforced polycarbonate
Degree of protection		IP54 NEMA Other
Dielectric strength		30 kV/mm, according to IEC 60243-1
Flammability characteristics		960 °C/1 mm thickness (base, cover; glow wire to VDE 0471 Part 2) 650 °C/1 mm thick (push-through membrane and seal material) to VDE 0471 Part 2)
Model		Surface mounting
Mounting depth		70 mm
Mounting weight capacity - max		0.7 kg
Product category		Empty enclosures
Suitable for		Emergency stop
Surface treatment		Resistant to corrosion
Track resistance		CTI 175 (base, to IEC 60112) CTI 175 (cover, to IEC 60112)
Type		Basic enclosure
Water consumption		0.29 % (According to DIN EN ISO 62)
<b>Ambient conditions, mechanical</b>		
Environmental resistance		Partly resistant to greases Partly resistant to acids (> 10%) Not resistant to Mineral oil Resistant against alkalis Resistant against alcohol Resistant against gasoline Resistant against salt solutions Resistant against greases Resistant against acids (< 10%)

		Partly resistant to alcohol Not resistant to benzene Resistant against benzene Chemical resistant (Base, Cover) Partly resistant to benzene Chemical resistant (Push-through membrane (CI-K1/CI-K2) and sealing material) Not resistant to alkalis Resistant against mineral oil
Impact resistance		IK06 (according to EN 50102)
Temperature resistance		-40 - 120 °C (enclosure) -40 - 80 °C (gasket)
<b>Climatic environmental conditions</b>		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Climatic proofing		Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
<b>Design verification</b>		
Equipment heat dissipation, current-dependent P <sub>vid</sub>		0 W
Heat dissipation capacity P <sub>diss</sub>		10 W
Heat dissipation per pole, current-dependent P <sub>vid</sub>		0 W
Rated operational current for specified heat dissipation (I <sub>n</sub> )		0 A
Static heat dissipation, non-current-dependent P <sub>vs</sub>		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Not applicable.
10.2.6 Mechanical impact		Meets the product standard's requirements.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Meets the product standard's requirements.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Is the panel builder's responsibility.
10.6 Incorporation of switching devices and components		Is the panel builder's responsibility.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Meets the product standard's requirements.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Empty enclosure for switchgear (EC000712)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Empty housing for switch devices (ec1@ss13-27-37-13-01 [AKN343019])			
Housing material			Plastic
Width	mm		100
Height	mm		100
Depth	mm		181
With transparent cover			No
Suitable for emergency stop			Yes
Model			Surface mounting
Degree of protection (IP)			IP54
Degree of protection (NEMA)			Other

