

Label, emergency switching off, yellow, HxW=50x33mm, emergency-Stop



Powering Business Worldwide™

Part no. M22-XZK-GB99

216472

EL Number  
(Norway)

4355429

| General specifications   |  |  |
|--|--|--|
| Product name   |  | Eaton Moeller® series M22 Accessory Emergency-Stop label           |
| Part no.   |  | M22-XZK-GB99   |
| EAN  |  | 4015082164720  |
| Product Length/Depth   |  | 50 millimetre  |
| Product height   |  | 1 millimetre   |
| Product width  |  | 33 millimetre  |
| Product weight   |  | 0.002 kilogram   |
| Compliances  |  | Contact Manufacturer   |
| Certifications   |  | UL/CSA certification not required<br>GL<br>LR<br>DNV               |
| Product Tradename  |  | M22  |
| Product Type   |  | Accessory  |
| Product Sub Type   |  | Emergency-Stop label   |
| Features & Functions   |  |  |
| Color  |  | Yellow   |
| Inscription  |  | Other  |
| Language   |  | English  |
| RAL-number   |  | 1004   |
| Shape  |  | Rectangular  |
| General information  |  |  |
| Degree of protection   |  | IP66   |
| Size   |  | 33 x 50 mm   |
| Climatic environmental conditions  |  |  |
| Ambient operating temperature - min  |  | -25 °C   |
| Ambient operating temperature - max  |  | 70 °C  |
| Communication  |  |  |
| Connection to SmartWire-DT   |  | No   |
| Design verification  |  |  |
| Equipment heat dissipation, current-dependent Pvid                               |  | 0 W  |
| Heat dissipation capacity Pdis   |  | 0 W  |
| Heat dissipation per pole, current-dependent Pvid                                |  | 0 W  |
| Rated operational current for specified heat dissipation (In)                    |  | 0 A  |
| Static heat dissipation, non-current-dependent Pvs                               |  | 0 W  |
| 10.2.2 Corrosion resistance  |  | Meets the product standard's requirements.                         |
| 10.2.3.1 Verification of thermal stability of enclosures                         |  | Meets the product standard's requirements.                         |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat       |  | Meets the product standard's requirements.                         |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects |  | Meets the product standard's requirements.                         |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                 |  | Please enquire   |
| 10.2.5 Lifting   |  | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact   |  | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions  |  | Meets the product standard's requirements.                         |
| 10.3 Degree of protection of assemblies  |  | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances   |  | Meets the product standard's requirements.                         |
| 10.5 Protection against electric shock   |  | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components                           |  | Does not apply, since the entire switchgear needs to be evaluated. |

|  |  |  |  |
|--|--|--|--|
| 10.7 Internal electrical circuits and connections        |  |  | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors                 |  |  | Is the panel builder's responsibility.   |
| 10.9.2 Power-frequency electric strength                 |  |  | Is the panel builder's responsibility.   |
| 10.9.3 Impulse withstand voltage                         |  |  | Is the panel builder's responsibility.   |
| 10.9.4 Testing of enclosures made of insulating material |  |  | Is the panel builder's responsibility.   |
| 10.10 Temperature rise                                   |  |  | Not applicable.  |
| 10.11 Short-circuit rating                               |  |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.           |
| 10.12 Electromagnetic compatibility                      |  |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.           |
| 10.13 Mechanical function                                |  |  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

## Technical data ETIM 9.0

|  |  |    |             |
|--|--|----|-------------|
| Low-voltage industrial components (EG000017) / Text plate for command devices (EC000624)   |  |    |             |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Identification plate for command devices (ecl@ss13-27-37-12-25 [AKF043019]) |  |    |             |
| Literal imprint  |  |    | Other       |
| Language of the imprint  |  |    | English     |
| Imprint ISO symbols  |  |    | None        |
| Colour   |  |    | Yellow      |
| Shape  |  |    | Rectangular |
| Width  |  | mm | 33          |
| Height   |  | mm | 1           |
| Outer diameter   |  | mm | 0           |