

**Housing, Pushbutton actuators, Indicator lights, Enclosure, momentary, 2 NC, 2 N/O, Screw connection, Number of locations 2, Grey, inscribed, Bezel: titanium**

**Part no. M22-I3-M2**  
**216533**  
**EL Number 4355304**  
**(Norway)**

<b>General specifications</b>		
Product name		Eaton Moeller® series M22 Housing
Part no.		M22-I3-M2
EAN		4015082165338
Product Length/Depth		80 millimetre
Product height		70 millimetre
Product width		153 millimetre
Product weight		0.317 kilogram
Compliances		Contact Manufacturer
Certifications		UL 508 IEC/EN 60947-5 VDE 0660 UL File No.: E29184 CE CSA File No.: 012528 CSA-C22.2 No. 14-05 CSA Class No.: 3211-03 UL IEC/EN 60947 CSA CSA-C22.2 No. 94-91 UL Category Control No.: NKCR
Product Tradename		M22
Product Type		Housing
Product Sub Type		None
Catalog Notes		85 - 264 V AC Contacts with safety function, by positive opening to IEC/EN 60947-5-1 LED element
<b>Features &amp; Functions</b>		
Bezel color		Titanium
Color		Light gray
Design		Enclosure
Enclosure color		Gray
Enclosure material		Plastic
Inscription		Inscribed
Knockouts		2 x M20 (cable entry knockouts at the base) 2 x M25/20 (cable entry knockouts at the side)
Light color		White
Number of locations		2
RAL-number		7035
<b>General information</b>		
Degree of protection		IP67/IP69K NEMA 4X, 13
Lifespan		5,000,000 mechanical Operations
Operating frequency		3600 Operations/h
Product category		RMQ-Titan
Size		Front dimensions: 153 x 80 mm
Type		Indicator lights Pushbutton actuator
<b>Ambient conditions, mechanical</b>		
Mounting position		As required
Shock resistance		Mechanical, According to IEC/EN 60068-2-27 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

<b>Climatic environmental conditions</b>		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Climatic proofing		Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
<b>Electrical rating</b>		
Rated control supply voltage (Us) at AC, 50 Hz - min		85 V
Rated control supply voltage (Us) at AC, 50 Hz - max		264 V
Rated control supply voltage (Us) at AC, 60 Hz - min		85 V
Rated control supply voltage (Us) at AC, 60 Hz - max		264 V
Rated control supply voltage (Us) at DC - min		0 V
Rated control supply voltage (Us) at DC - max		0 V
<b>Short-circuit rating</b>		
Rated conditional short-circuit current (Iq)		1 kA
<b>Communication</b>		
Connection to SmartWire-DT		No
Connection type		Screw connection
<b>Actuator</b>		
Actuating force		5 N
Actuator color		Red/white/green
Actuator function		Momentary
Actuator travel and actuation force (DIN EN 60947-5-1)		4.8 mm
Knob travel		5.7 mm
<b>Contacts</b>		
Force for positive opening - min		15 N
Number of contacts (change-over contacts)		0
Number of contacts (normally closed contacts)		2
Number of contacts (normally open contacts)		2
<b>Design verification</b>		
Equipment heat dissipation, current-dependent Pvid		0 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		0.11 W
Rated operational current for specified heat dissipation (In)		6 A
Static heat dissipation, non-current-dependent Pvs		1 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Control circuit devices combination in enclosure (EC000225)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Command and alarm device combination in housing (ec@ss13-27-37-12-16 [AKF034019])

Number of command positions			3
Number of push buttons			2
Number of indicator lights			1
Number of key switches			0
Number of selector switches			0
Number of mushroom-shaped push-buttons			0
Suitable for emergency stop			No
Rated control supply voltage AC 50 Hz		V	85 - 264
Rated control supply voltage AC 60 Hz		V	85 - 264
Rated control supply voltage DC		V	0 - 0
Power consumption		W	
Colour housing cover			Grey
Housing colour			Grey
Housing material			Plastic
Number of contacts as normally open contact			2
Number of contacts as normally closed contact			2
Number of contacts as change-over contact			0
Degree of protection (IP)			IP67/IP69K
Degree of protection (NEMA)			4X, 13