

Insulated enclosure, for PKZ0, +cut-out 45mm, IP40_x



Part no. CI-K2-PKZ0
219653
EL Number 4355085
(Norway)

General specifications		
Product name		Eaton Moeller® series CI-K Accessory Insulated enclosure
Part no.		CI-K2-PKZ0
EAN		4015082196530
Product Length/Depth		105 millimetre
Product height		180 millimetre
Product width		100 millimetre
Product weight		0.33 kilogram
Compliances		Contact Manufacturer
Certifications		CE
Product Tradename		CI-K
Product Type		Accessory
Product Sub Type		Insulated enclosure
Catalog Notes		Additional cable insertion membrane as cable entry gland: 2 x in the rear wall and 1 x at the bottom.
Features & Functions		
Enclosure material		Plastic
Fitted with:		N and PE terminal Cover with aperture dimensioned to accommodate front of breaker
Knockouts		2 x M25 (cable entry knockout at the top) 2 x M25 (cable entry knockout at the bottom)
General information		
Degree of protection		IP41, when mounted vertically IP40 NEMA Other
Degree of protection (front side)		IP40
Model		Surface mounting
Product category		Accessories
Used with		PKZ0 +L-PKZ0 (2 units), +NHI or AGM, +U or A, PKZM0-...
Climatic environmental conditions		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Design verification		
Equipment heat dissipation, current-dependent P _{vid}		0 W
Heat dissipation capacity P _{diss}		10 W
Heat dissipation per pole, current-dependent P _{vid}		0 W
Rated operational current for specified heat dissipation (I _n)		0 A
Static heat dissipation, non-current-dependent P _{vs}		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Empty enclosure for switchgear (EC000712)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Empty housing for switch devices (ecl@ss13-27-37-13-01 [AKN343019])		
Housing material		Plastic
Width	mm	100
Height	mm	180
Depth	mm	105
With transparent cover		No
Suitable for emergency stop		No
Model		Surface mounting
Degree of protection (IP)		IP40
Degree of protection (NEMA)		Other