

Off switch, 1p, 40A

Part no. ZP-A40/1
248263

General specifications		
Product name		Eaton Distribution parts
Part no.		ZP-A40/1
EAN		4015082482633
Product Length/Depth		80 millimetre
Product height		75 millimetre
Product width		18 millimetre
Product weight		0.093 kilogram
Compliances		RoHS conform
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Product Specification Details		
Built-in depth		60 mm
Color calotte		Other
Degree of protection		IP40
Imprint/indication		Symbol "arrows"
Lamp power		0 W
Lamp socket		Other
Lamp type		Other
Number of contacts (change-over contacts)		0
Number of contacts (normally closed contacts)		1
Number of contacts (normally open contacts)		1
Number of poles		Single-pole
Rated operational voltage (Ue) - max		400 V
Rated short-time withstand current (Icw)		3 kA
Rated switching capacity		0 kA
Switch type		Off switch
Voltage rating - min		230 V
Voltage type		AC
Width in number of modular spacings		1

Technical data ETIM 9.0

Devices for distribution board-/surface mounting (EG000062) / Main switch for distribution board (EC001545)

Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Main switch for distribution board (ecl@ss13-27-14-23-01 [AFZ813019])

Switching function		Off switch
Number of contacts as normally open contact		1
Number of contacts as normally closed contact		1
Number of contacts as change-over contact		0
Number of poles		1
Rated current	A	40
Rated voltage	V	400
Min. rated voltage	V	230
Rated switching capacity	kA	0
Short-circuit breaking capacity (Icw)	kA	3

Voltage type			AC
With signal lamp			No
Colour calotte			Other
Lamp type			Other
Lamp socket			Other
Max. lamp power		W	0
Width in number of modular spacings			1
Built-in depth		mm	60
Degree of protection (IP)			IP40
Imprint/indication			Symbol "arrows"
Forced segregation according to DIN VDE 0113			No