

Insulated enclosure, IP55_x, rotary handle red yellow, for PKZ0



Part no. CI-PKZ0-GRM
260104

General specifications		
Product name		Eaton Moeller® series CI Insulated enclosure
Part no.		CI-PKZ0-GRM
EAN		4015082601041
Product Length/Depth		25 millimetre
Product height		160 millimetre
Product width		80 millimetre
Product weight		0.2 kilogram
Compliances		Contact Manufacturer
Certifications		CE
Product Tradename		CI
Product Type		Insulated enclosure
Product Sub Type		None
Features & Functions		
Enclosure material		Plastic
Fitted with:		Red-yellow rotary knob, for use as EMERGENCY STOP switch (according to EN 60204) PE(N) terminal
Knockouts		Hard mirror with cable entry knockouts (can be cut out) 2 x M25 (cable entry knockout with thread at the top) 2 x M25 (cable entry knockout with thread at the bottom) 2 x M20 (cable entry knockouts at the rear)
General information		
Degree of protection		IP55 NEMA Other
Model		Surface mounting
Product category		Accessories
Suitable for		Emergency stop
Used with		PKZM0 +L-PKZ0 (2 units), +NHI or U or A, PKZM0-...
Climatic environmental conditions		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Design verification		
Equipment heat dissipation, current-dependent P _{vid}		0 W
Heat dissipation capacity P _{diss}		10 W
Heat dissipation per pole, current-dependent P _{vid}		0 W
Rated operational current for specified heat dissipation (I _n)		0 A
Static heat dissipation, non-current-dependent P _{vs}		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Empty enclosure for switchgear (EC000712)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Empty housing for switch devices (ecl@ss13-27-37-13-01 [AKN343019])			
Housing material			Plastic
Width		mm	80
Height		mm	160
Depth		mm	25
With transparent cover			No
Suitable for emergency stop			Yes
Model			Surface mounting
Degree of protection (IP)			IP55
Degree of protection (NEMA)			Other